

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

Important! Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

2006 Embroidered Corset

Recommendations on fabric: stiff satin.

You will also need: separating zip, metallic/plastic bones, lace appliqué/embroidery, fusing, cords for loops.

CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.



Seam allowances: 2 cm for middle back seam (to stitch the zipper). 1 cm for other seams.

Main fabric:

Satin:

1. All corset pieces. Use also as lining.

Fusing:

1. All corset pieces.

Lace/trimming: sew to ready front parts and bead by hands.

INSTRUCTIONS:

1. Insert metal or plastic bones that are 2 cm shorter than the seam length (for more comfortable sewing) into the bodice seams.
2. The zipper is placed in the center back seam.
3. Fastening: two small buttons with cord loops at the back of the collar.

Congratulations, your corset is ready! :)