

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

Important! Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

2019 Coat from crêpe and atlas

Recommendations on fabric: crepe and atlas in the same color.

You will also need: fusible interfacing, 1 button.

CUTTING:

The word, "beam" used on some patterns means "straight of grain". Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.



Main fabric:

Crepe:

1. Central back part - 2 details
2. Side back part - 2 details
3. Central left front part - 1 detail
4. Side front part - 2 details
5. Inset of front part - 1 detail
6. Upper collar – 3 details (2 of them symmetrical)
7. Lower collar – 1 detail
8. Sleeve – 2 details

Atlas:

1. Central right front part - 1 detail
2. Back yoke - 2 details
3. Yoke of front part - 2 details
4. Cuff – 2 details

Lining is made of atlas and is the same as main garment. All details of main fabric are strengthened with fusing.

INSTRUCTIONS:

1. Sew yokes of back part and of front part for main garment and for lining. Press apart seams. Overstitch yoke with lining.
2. Sew central and side parts of back part, and also the middle seam. Press the seams.
3. Sew details of right and left front parts. Sew details of collar along central edge: right and left top collar, top and lower collar. Stitch lower collar to right front part along front vertical edge. Overstitch lower collar with upper collar, turn and press. Stitch collar to back part and front part. Stitch yoke to seam of sewing in the collar.
4. Sew details of sleeve. Sew in sleeves into armholes, easing in along the cap.
5. Sew details of lining. Overstitch buttonhole. Overstitch coat with lining.

Congratulations, your coat is ready! :)