

If the pattern has a double line around it, the seam allowances are included.

**Note:** By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

**Important!** Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

## 2070 Blazer with Dropped Shoulders

Recommendations on fabric: boucle natural/mixed suiting fabrics.

You will also need: fusible interfacing; lining; 4 buttons.

### CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Seam allowances: all seams 1 cm. Seam allowance for hem of garment and hem of sleeve – 3 cm.

### Main fabric:

1. Back – cut 2
2. Front – cut 2
3. Center front facing – cut 2
4. Lower collar – cut 1
5. Upper collar – cut 1
6. Back neck facing – cut 1



7. Sleeve – cut 2
8. Off-set welt – cut 2

Lining:

1. Back – cut 2
2. Front – cut 2
3. Sleeve – cut 2

**Attention!** Front and back from lining are cut using the pattern blocks for self fabric, with the exception for the areas of center front facing and back neckline facing.

Fusible interfacing:

1. Front – cut 2
2. Center front facing – cut 2
3. Back neck facing – cut 1
4. Upper collar – cut 1
5. Off-set welt – cut 2

INSTRUCTIONS:

1. Apply fusible interfacing. Apply fusing to the front along the lapel fold; the width should be 1 cm.
2. Sew waist darts on the backs; press the bulk toward the center. Sew bust darts on the fronts, trim the bulk to 1 cm, and press toward the center.
3. Sew the center back seam; press the seam open.
4. Fold the off-set welt in half lengthwise, right sides together, and sew along one short side. Trim the corners, turn the piece right side out, and press. Pin the off-set welt to the front along the lower marking line (the fold should be directed downward) and sew. Fold the off-set welt upward, press, and topstitch the side edge to the front.
5. Sew and press open the shoulder and side edges.
6. Pin the upper collar to the lower collar and sew the corners and fall. Start and stop stitching exactly at the marked seam line between the collar and the garment. Trim the corners and clip into the seam allowance near the notch. Turn the collar right side out, straighten, and press.
7. Sew and press open the shoulder seams of the back neckline facing and buttonstand.

8. Place the center front facing onto the front, right sides together. Pin and sew along the center front edge, sewing upward to the notch marking the end of the collar seam. Trim the corners. Topstitch the seam allowance along the center front edge – onto the center front facing along the closure, and onto the front along the part that is folded away. Place the stitch line 0.2 cm from the seam. Turn the buttonstands (center front edges) right side out and straighten the seams.
9. Sew the lower collar into the neckline of the jacket. Sew the upper collar into the neckline of the back facing and center front facing. Press the seam allowances of the collar seam open and slipstitch them together close to the seam.
10. Sew the elbow seam on the sleeve; press the seam open. Press the hem of the sleeve. Sew and press open the front sleeve seam. Sew the sleeves into the armholes, matching notches.
11. Sew the seams on the lining and sew in the sleeves, leaving an opening for turning on the front right sleeve seam.
12. Sew the lining to the inner edges of the buttonstands and to the back neckline facing. Sew the lining to the jacket hem. Turn the jacket right side out through the opening in the sleeve seam. Sew the lining to the sleeve hem. Sew the opening in the sleeve closed.
13. Make buttonholes on the right front; sew buttons on the left front.

Congratulations, your blazer is ready! :)