

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

Important! Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

2079 Skirt with Yoke and Front Buttons

Recommendations on fabric: well draping natural/mixed fabrics.

You will also need: fusible interfacing; 9 buttons.

CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.



Seam allowances: all seams 1 cm. Seam allowance along hem – 2 cm.

Main fabric:

1. Back – cut 1 on fold
2. Back yoke – cut 1 on fold
3. Front skirt – cut 2
4. Front yoke – cut 2
5. Belt – cut 1
6. Placket – cut 2

Fusible interfacing:

1. Belt – cut 1
2. Placket – cut 2

INSTRUCTIONS:

1. Apply fusible interfacing to the belt.
2. Sew a gathering stitch along the upper edge of the back skirt and gather the fullness. Sew the yoke to the back skirt; serge and press upward.
3. Sew a gathering stitch along the upper edge of the front skirt and gather the fullness. Sew the yoke to the front; serge and press upward.
4. Sew and serge the side edges; press the seams toward the back.
5. Serge the hem of the skirt; press to the wrong side and topstitch.
6. Fold the placket in half lengthwise and sew the lower corner. Start and stop stitching exactly at the marked placket seam. Sew the outer side of the placket to the skirt. Fold under the seam allowance of the inner side and stitch-in-the-ditch along the seam of the outer side.
7. Sew the outer side of the belt to the upper edge of the skirt. Sew the ends of the belt, trim the corners, and turn right side out. Turn under the inner edge of the belt and stitch in the ditch. Press the belt.
8. Mark and make buttonholes. Sew on the buttons.

Congratulations, your skirt is ready! :)