

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

Important! Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

2095 Jersey Tunic with Small Collar

Recommendations on fabric: well draping natural/mixed knit fabrics of high to medium stretchiness.

You will also need: knit bias tape, knit fusible interfacing.

CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.



Seam allowances: seam allowance for hem of garment – 2 cm, other seams – 1 cm.

Main fabric:

1. Front – cut 1 on fold
2. Back – cut 2
3. Front yoke – cut 1
4. Collar – cut 2

Fusible interfacing:

1. Collar – cut 1

INSTRUCTIONS:

1. Apply fusible interfacing to the upper collar.
2. Sew the center back seam. Serge and press towards the left.
3. Sew a gathering stitch along the upper edge of the front and gather fullness. Sew the yoke to the upper edge of the front. Serge and press upwards.
4. Sew the shoulder and side seams, press seams towards the back, and serge.
5. Pin the collars right sides together and sew around the collar and collar fall. Clip into curves and trim away corners. Turn the collar right side out and press. Sew the outer edge of the collar into the neckline and press towards the collar. Fold the inner collar's seam allowance inside at 1 cm and stitch in the ditch.
6. Cut (or use ready-made) bias tape, 4 cm wide and as long as the armhole + 6 cm. Fold the bias tape in half lengthwise, right side out, and press. Pin the bias tape to the armhole edge from the right side and sew. Fold the bias tape onto the wrong side, clip into seam allowances, and topstitch onto the main piece along the seam. Press the seam.
7. Serge the lower edge of the garment, press onto the wrong side, and topstitch.

Congratulations, your tunic is ready! :)