

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

Important! Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

2138 Tunic Dress with Cowl Neckline

Recommendations on fabric: natural/mixed knit fabrics of medium or high stretchiness.

CUTTING:

The word, "beam" used on some patterns means "straight of grain". Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Seam allowances: seam allowance by срезу горловины and проймы – 1.5 cm, seam allowance along hem – 2 cm, other seams 1 cm.

Main fabric:

1. Front – cut 1 on fold
2. Back – cut 1 on fold

INSTRUCTIONS:

Advice: sew knit pieces with special elastic/zig-zag stitches. If you use an overlock, cut seam allowances to 0.6-0.8 cm width. Topstitch hem allowances with double needle to save elasticity.

1. Sew side and shoulder seams, serge, and press towards the back.
2. Serge the neckline, fold the seam allowance to the wrong side, and topstitch.
3. Serge seam allowances along the armhole, fold the seam allowance to the wrong side, and topstitch.
4. Serge the seam allowance for the hem, fold to the wrong side, and topstitch.
Congratulations – your tunic are finished! :)

