

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

Important! Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

2277 Jacket without lining

Recommendations on fabric:
natural/mixed suiting fabric.
You will also need: fusible
interfacing; 3 buttons.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Main fabric:

1. Side back – cut 2
2. Center back – cut 2
3. Center front – cut 2
4. Side front – cut 2
5. Back neck facing – cut 1
6. Center front facing – cut 2
7. Cuff – cut 2
8. Belt Loop – cut 1
9. Belt – cut 1

Fusible interfacing:

1. Back neck facing – cut 1
2. Center front facing – cut 2

3. Belt – cut 1
4. Cuff – cut 2

INSTRUCTIONS:

1. Apply fusible interfacing.
2. Sew side backs to center back. Serge seams and press towards center. Sew center back seam. Serge and press towards left.
3. Sew side fronts to center front. Serge seams and press towards center.
4. Sew shoulder and side seams of jacket sewing the sleeve edges at the same time. Serge seams and press towards back.
6. Sew and press apart shoulder seams of back neckline facing and buttonstand. Serge outer edge.
7. Pin center front facing onto front, right sides together, and sew along the hem, center front edge, lapel, back neckline. Clip seam allowances, trim away corner. Center front facing and fold facing onto wrong side and press. Slip stitch facing to shoulder seams.
8. Sew cuff into a ring, press seam apart. Pin cuff to garment right sides together and sew cuff to garment. Fold cuff onto wrong side and press. Turn under the inner edge and topstitch onto sleeve. Fold away hem of sleeve onto right side, straightening the cuff.
9. Serge the hem of jacket, fold inside onto wrong side and topstitch.
10. Serge one longer edge of the belt loop. Fold belt loop so that it has 3 layers in total and topstitch along longer sides. Cut belt loop into 4 pieces. Topstitch belt loops onto princess seams at the waist level.
11. On right front make buttonholes and sew on buttons on left front.
12. Fold belt in half lengthwise right sides together and sew, and leave an opening unsewn along the lower edge, so that you can turn out the piece later. Turn belt right side out, straighten and press. Sew the opening closed.

Congratulations, your jacket is ready! :)