

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guide lines are printed on pattern

Important! Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

2301 Blouse With Trimming

Recommendations on fabric:
natural/mixed fabrics suitable for
blouses/dresses in 2 contrasting or
matching colors.



You will also need: fusible interfacing;
dress zipper. Seam allowances: all seams
1 cm.

CUTTING:

Note on cutting:

On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.

When sewing the garment, pay attention to notches, they must match up.

Fabric 1:

Back - cut 2

Front - cut 1

Side front - cut 1

Sleeve - cut 2

Back neck facing – cut 2
Front neck facing – cut 1

Fabric 2:
Cuff - cut 2
Front decoration – cut 2
Side front decoration – cut 2
Back decoration – cut 2

Fusible interfacing:
Back neck facing – cut 2
Front neck facing – cut 1
Cuff - cut 2

INSTRUCTIONS:

1. Apply fusible interfacing.
2. Serge center back edges separately on each piece. Sew center seam from notch for zipper down to hem, press seam apart. Sew in zipper.
3. Sew darts on front. Press bulk towards top.
4. Sew shoulder seams, press seams towards back and serge.
5. Serge upper edges of inner decorations.
6. Pin side decorations together right sides together and sew lower edge. Turn pieces right side out and press. Sew outer decoration to side front. Press towards trimming. Topstitch inner decoration into the seam of outer decoration.
7. Pin front decorations together right sides together and sew lower edge. Turn right side out and press. Sew outer decoration to the lower edge of front. Press towards trimming. Pin front onto side part and topstitch front into the seam of decoration up to the side seam.
8. Pin back decorations right sides together and sew lower edge. Turn right side out and press. Sew outer decoration to the lower edge of back. Press towards trimming. Pin front onto back, right sides together, and sew side seams. Topstitch back decoration into the seam of outer decoration.

9. Sew shoulder seams of neck facings, press seam apart. Serge outer edge. Pin facing to garment right sides together and sew the neckline. Clip into curves, turn facing under, straighten, press. Slipstitch to shoulder seams and to zipper tape.
10. Sew sleeve seam, press seams towards back and serge. Sew sleeves into armholes, matching notches, serge.
11. Sew cuff into a ring, press seam apart. Fold cuff in half lengthwise and press right side out. Sew cuff to wrong side of sleeve, serge.