

If the pattern has a double line around it, the seam allowances are included.

**Note:** By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

**Important!** Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

## 2367 Sweatshirt with Draped Sleeves

Recommendations on fabric: natural/mixed knit fabric of small stretchiness.

You will also need: rib knit fabric or knit fabric of high stretchiness.

### CUTTING:

The word, "beam" used on some patterns means "straight of grain". Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Seam allowances: all seams 1 cm.

### Main fabric:

1. Back – cut 1 on fold
2. Front – cut 1 on fold
3. Sleeve – cut 2

### Main fabric 1:

1. Hem facing – cut 1 on fold
2. Cuff – cut 2
3. Neckline facing – cut 1



## INSTRUCTIONS:

Advice: sew knit pieces with special elastic/zig-zag stitches. If you use an overlock, cut seam allowances to 0.6-0.8 cm width. Topstitch hem allowances with double needle to save elasticity.

1. Sew a gathering stitch along the front armhole edge of the sleeve and along the back armhole edge of the sleeve. Gather the fullness evenly.
2. Sew the sleeve to the back. Press the seam allowances toward the sleeve and serge. Sew the sleeve to the front. Press the seam allowances toward the sleeve and serge.
3. Sew the sleeve seam and side seam in one continuous seam. Press the seam allowances toward the back and serge.
4. Sew the neckline band into a ring and press the seam allowances open. Fold the band in half lengthwise, wrong sides together, and press. Sew the neckline band to the neckline, stretching it slightly to fit. Serge the seam allowances and press.
5. Sew a gathering stitch along the lower edge of the sleeve and gather the fullness evenly. Sew the cuff into a ring and press the seam allowances open. Fold the cuff in half lengthwise, right side out, and press. Sew the cuff to the lower edge of the sleeve. Serge the seam allowances and press.
6. Sew the hem band into a ring and press the seam allowances open. Fold the band in half lengthwise, wrong sides together, and press. Sew the band to the lower edge of the garment, positioning the seam below the left side seam and stretching the band slightly to fit. Serge the seam allowances and press.

Congratulations – your sweatshirt are finished! :)