

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

Important! Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

2403 Skirt with Asymmetric Front Pleat

Recommendations on fabric: thick natural/mixed fabrics suitable for skirts.

You will also need: fusible interfacing; 1 button; dress zipper.

CUTTING:

The word, "beam" used on some patterns means "straight of grain". Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Seam allowances: all seams 1 cm. Seam allowance along hem 2 cm.

Main fabric:

1. Front skirt – cut 1
2. Back – cut 1 on fold
3. Belt – cut 1

Fusible interfacing:

1. Belt – cut 1



INSTRUCTIONS:

1. Apply fusible interfacing to the belt.
2. Make a pleat on the front skirt. Baste the pleat according to the technical drawing and topstitch from the right side, from the top to the horizontal marking.
3. Serge the left side edges separately. Sew the seam from the zipper marker down to the hem. Press the seam apart. Sew in the zipper.
4. Sew and serge the right side edges, pressing the seams towards the back.
5. Sew the outer side of the belt to the upper edge of the skirt. Sew the ends of the belt, trim corners, and turn right side out. Turn the inner edge of the belt under and stitch in the ditch. Press the belt.
6. Mark and make a button loop. Sew on the button.
7. Serge the hem of the skirt, press onto the wrong side, and topstitch.

Congratulations, your skirt is ready! :)