

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

Important! Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

1. Apply fusible interfacing.
2. Sew shoulder seams, press seam apart.
3. Trace lines to mark the slit for opening on the right side of the right inner centre front facing: the first line is parallel to the centre front edge and is at 1.5 cm from the centre front edge when ready; the second and the third lines mark the length of closure. Pin lining with fusible interfacing attached onto right side of centre front edge, right sides together, directed away from the centre front edge, matching the edge of lining with the marked line. Sew a stitch line at 0.5 cm from the marked line, along the closure slit, up to the lines, marking the length of closure. Pin the second lining of closure next to the stitch line of the first lining, and sew at 0.5 cm. Make sure that the linings are stitched correctly from the wrong side (stitch lines should be parallel).
Slash

the opening. Make slanted cuts at 1-1.5 cm from the end of the slit of closure. Fold linings onto the wrong side

through the opening, making a frame of the lining with fusible interfacing, its width is equal to the width between the stitch lines. Sew a stitch line into the seam of lining (stitch in the ditch to fix the layers). Fold the

second lining towards the inner edge of Center Front facing and press and sew a fixing stitch at 0.1 cm from seam of lining. Mark and make buttonholes. Make buttonholes on the Center Front facing, through the main fabric and the lining with fusible interfacing. Straighten and fix the ends of closure with a double stitch line from

the wrong side, at the corners. Sew edges of lining. Sew fixing stitches between each pair of button holes, the

length of the fixing stitch is equal to the width of frame. Press the inner centre front facing. Cut away the excess of lining.

4. Sew center seams on collar on inner and outer Center Front facings, press seam apart. Pin outer Center Front

facings to inner Center Front facings right sides together and sew outer edge. Clip seam allowances, fold away

the inner Center Front facing and press.

5. Sew Center Front facings to fronts and to backs, clipping into seam allowances near corners. Serge seam



allowances. Press towards the main piece.

6. Sew sleeves into armholes. Serge and press onto sleeve. Sew side seams and sleeve seams continuously. Serge seams and press towards back.

7. Serge seam allowance for hem of garment and hem of sleeve, fold inside and press and topstitch.

8. Fold belt in half lengthwise, sew along one longer and shorter sides, leaving an opening for turning. Trim away corners, turn right side out and press. Sew the opening closed. 1. Apply fusible interfacing. 2. Sew shoulder seams, press seam apart. 3. Trace lines to mark the slit for opening on the right side of the right inner centre front facing: the first line is parallel to the centre front edge and is at 1.5 cm from the centre front edge when ready; the second and the third lines mark the length of closure. Pin lining with fusible interfacing attached onto right side of centre front edge, right sides together, directed away from the centre front edge, matching the edge of lining with the marked line. Sew a stitch line at 0.5 cm from the marked line, along the closure slit, up to the lines, marking the length of closure. Pin the second lining of closure next to the stitch line of the first lining, and sew at 0.5 cm. Make sure that the linings are stitched correctly from the wrong side (stitch lines should be parallel). Slash the opening. Make slanted cuts at 1-1.5 cm from the end of the slit of closure. Fold linings onto the wrong side through the opening, making a frame of the lining with fusible interfacing, its width is equal to the width between the stitch lines. Sew a stitch line into the seam of lining (stitch in the ditch to fix the layers). Fold the second lining towards the inner edge of Center Front facing and press and sew a fixing stitch at 0.1 cm from seam of lining. Mark and make buttonholes. Make buttonholes on the Center Front facing, through the main fabric and the lining with fusible interfacing. Straighten and fix the ends of closure with a double stitch line from the wrong side, at the corners. Sew edges of lining. Sew fixing stitches between each pair of button holes, the length of the fixing stitch is equal to the width of frame. Press the inner centre front facing. Cut away the excess of lining.

4. Sew center seams on collar on inner and outer Center Front facings, press seam apart. Pin outer Center Front facings to inner Center Front facings right sides together and sew outer edge. Clip seam allowances, fold away the inner Center Front facing and press. 5. Sew Center Front facings to fronts and to backs, clipping into seam allowances near corners. Serge seam allowances. Press towards the main piece. 6. Sew sleeves into armholes. Serge and press onto sleeve. Sew side seams and sleeve seams continuously. Serge seams and press towards back. 7. Serge seam allowance for hem of garment and hem of sleeve, fold inside and press and topstitch. 8. Fold belt in half lengthwise, sew along one longer and shorter sides, leaving an opening for turning. Trim away corners, turn right side out and press. Sew the opening closed. 1. Apply fusible interfacing. 2. Sew shoulder seams, press seam apart. 3. Trace lines to mark the slit for opening on the right side of the right inner centre front facing: the first line is parallel to the centre front edge and is at 1.5 cm from the centre front edge when ready; the second and the third lines mark the length of closure. Pin lining with fusible interfacing attached onto right side of centre front edge, right sides together, directed away from the centre front edge, matching the edge of lining with the marked line. Sew a stitch line at 0.5 cm from the marked line, along the closure slit, up to the lines, marking the length of closure. Pin the second lining of closure next to the stitch line of the first lining, and sew at 0.5 cm. Make sure that the linings are stitched correctly from the wrong side (stitch lines should be parallel). Slash the opening. Make slanted cuts at 1-1.5 cm from the end of the slit of closure. Fold linings onto the wrong side through the opening, making a frame of the lining with fusible interfacing, its width is equal to the width between the stitch lines. Sew a stitch line into the seam of lining (stitch in the ditch to fix the layers). Fold the second lining towards the inner edge of Center Front facing and press and sew a fixing stitch at 0.1 cm from seam of lining. Mark and make buttonholes. Make buttonholes on the Center Front facing, through the main fabric and the lining with fusible interfacing. Straighten and fix the ends of closure with a double stitch line from the wrong side, at the corners. Sew edges of lining. Sew fixing stitches between each pair of button holes, the length of the fixing stitch is equal to the width of frame. Press the inner centre front facing. Cut away the excess of lining.

4. Sew center seams on collar on inner and outer Center Front facings, press seam apart. Pin outer Center Front facings to inner Center Front facings right sides together and sew outer edge. Clip seam allowances, fold away the inner Center Front facing and press. 5. Sew Center Front facings to fronts and to backs, clipping into seam allowances near corners. Serge seam allowances. Press towards the main piece. 6. Sew sleeves into armholes. Serge and press onto sleeve. Sew side seams and sleeve seams continuously. Serge seams and press towards back. 7. Serge seam allowance for hem of garment and hem of sleeve, fold inside

and press and topstitch. 8. Fold belt in half lengthwise, sew along one longer and shorter sides, leaving an opening for turning. Trim away corners, turn right side out and press. Sew the opening closed. 1. Apply fusible interfacing. 2. Sew shoulder seams, press seam apart. 3. Trace lines to mark the slit for opening on the right side of the right inner centre front facing: the first line is parallel to the centre front edge and is at 1.5 cm from the centre front edge when ready; the second and the third lines mark the length of closure. Pin lining with fusible interfacing attached onto right side of centre front edge, right sides together, directed away from the centre front edge, matching the edge of lining with the marked line. Sew a stitch line at 0.5 cm from the marked line, along the closure slit, up to the lines, marking the length of closure. Pin the second lining of closure next to the stitch line of the first lining, and sew at 0.5 cm. Make sure that the linings are stitched correctly from the wrong side (stitch lines should be parallel). Slash the opening. Make slanted cuts at 1-1.5 cm from the end of the slit of closure. Fold linings onto the wrong side through the opening, making a frame of the lining with fusible interfacing, its width is equal to the width between the stitch lines. Sew a stitch line into the seam of lining (stitch in the ditch to fix the layers). Fold the second lining towards the inner edge of Center Front facing and press and sew a fixing stitch at 0.1 cm from seam of lining. Mark and make buttonholes. Make buttonholes on the Center Front facing, through the main fabric and the lining with fusible interfacing. Straighten and fix the ends of closure with a double stitch line from the wrong side, at the corners. Sew edges of lining. Sew fixing stitches between each pair of button holes, the length of the fixing stitch is equal to the width of frame. Press the inner centre front facing. Cut away the excess of lining. 4. Sew center seams on collar on inner and outer Center Front facings, press seam apart. Pin outer Center Front facings to inner Center Front facings right sides together and sew outer edge. Clip seam allowances, fold away the inner Center Front facing and press. 5. Sew Center Front facings to fronts and to backs, clipping into seam allowances near corners. Serge seam allowances. Press towards the main piece. 6. Sew sleeves into armholes. Serge and press onto sleeve. Sew side seams and sleeve seams continuously. Serge seams and press towards back. 7. Serge seam allowance for hem of garment and hem of sleeve, fold inside and press and topstitch. 8. Fold belt in half lengthwise, sew along one longer and shorter sides, leaving an opening for turning. Trim away corners, turn right side out and press. Sew the opening closed. **Tunica with belt**

Recommendations on fabric: natural/mixed suiting fabrics.

You will also need: fusible interfacing; 5 buttons; lining.

CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Seam allowances: all seams 1 cm. Seam allowance for hem of garment and hem of sleeve – 3.5 cm.

Main fabric:

1. Back – cut 1 on fold
2. Front – cut 2
3. Sleeve – cut 2
4. Center front facing – cut 4
5. Belt – cut 1 on fold

Fusible interfacing:

1. Center front facing – cut 2
2. Lining of hidden button panel – cut 1

Lining:

1. Lining of hidden button panel – cut 2

INSTRUCTIONS:

1. Apply fusible interfacing.
2. Sew shoulder seams, press seam apart.
3. Trace lines to mark the slit for opening on the right side of the right inner centre front facing: the first line is parallel to the centre front edge and is at 1.5 cm from the centre front edge when ready; the second and the third lines mark the length of closure. Pin lining with fusible interfacing attached onto right side of centre front edge, right sides together, directed away from the centre front edge, matching the edge of lining with the marked line. Sew a stitch line at 0.5 cm from the marked line, along the closure slit, up to the lines, marking the length of closure. Pin the second lining of closure next to the stitch line of the first lining and sew at 0.5 cm. Make sure that the linings are stitched correctly from the wrong side (stitch lines should be parallel). Slash the opening. Make slanted cuts at 1-1.5 cm from the end of the slit of closure. Fold linings onto the wrong side through the opening, making a frame of the lining with fusible interfacing, its width is equal to the width between the stitch lines. Sew a stitch line into the seam of lining (stitch in the ditch to fix the layers). Fold the second lining towards the inner edge of Center Front facing and press and sew a fixing stitch at 0.1 cm from seam of lining. Mark and make buttonholes. Make buttonholes on the Center Front facing, through the main fabric and the lining with fusible interfacing. Straighten and fix the ends of closure with a double stitch line from the wrong side, at the corners. Sew edges of lining. Sew fixing stitches between each pair of buttonholes, the length of the fixing stitch is equal to the width of frame. Press the inner centre front facing. Cut away the excess of lining.
4. Sew center seams on collar on inner and outer Center Front facings, press seam apart. Pin outer Center Front facings to inner Center Front facings right sides together and sew outer edge. Clip seam allowances, fold away the inner Center Front facing and press.
5. Sew Center Front facings to fronts and to backs, clipping into seam allowances near corners. Serge seam allowances. Press towards the main piece.

6. Sew sleeves into armholes. Serge and press onto sleeve. Sew side seams and sleeve seams continuously. Serge seams and press towards back.
7. Serge seam allowance for hem of garment and hem of sleeve, fold inside and press and topstitch.
8. Fold belt in half lengthwise, sew along one longer and shorter sides, leaving an opening for turning. Trim away corners, turn right side out and press. Sew the opening closed.

Congratulations, your tunic is ready :)