

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

Important! Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

2485 Tunic with Shaped Armholes

Recommendations on fabric: natural/mixed fabrics suitable for blouses.

You will also need: dress zipper, fusible interfacing.

CUTTING:

The word, "beam" used on some patterns means "straight of grain". Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Seam allowances: all seams 1 cm. Seam allowance along hem – 1.5 cm.

Main fabric:

1. Back – cut 2
2. Front – cut 1 on fold
3. Front lining – cut 1 on fold
4. Back lining – cut 2

Fusible interfacing:

1. Front lining – cut 1 on fold
2. Back lining – cut 2



INSTRUCTIONS:

1. Apply fusible interfacing.
2. Sew the shoulder and side seams of the upper part. Press the shoulder seam allowances open. Serge the side seam allowances and press them toward the back.
3. Construct the lining in the same way. Serge the lower edge of the lining, turn it to the wrong side, and topstitch.
4. Pin the lining to the garment, right sides together, and sew the neckline. Clip the seam allowances, turn the lining to the inside, and press.
5. Sew the lining to the armholes in two steps: first sew the front armhole, then the back armhole. Clip into the seam allowances and press.
6. Slipstitch the center edges of the garment and lining together. Serge the center edges separately. Sew the center back seam from the zipper notch to the hem. Press the seam allowances open and insert the zipper.
7. Serge the lower edge of the garment, press it to the wrong side, and topstitch.

Congratulations – your tunic are finished! :)