

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

Important! Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

2487 Dress with asymmetric details

Recommendations on fabric: Natural/mixed dress fabrics in contrasting or similar colors.

You will also need: fusible interfacing, dress zipper.

CUTTING:

The word, "beam" used on some patterns means "straight of grain". Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Seam allowances: all seams 1 cm, seam allowance for hem of garment - 2.0 cm, seam allowance for hem of sleeve - 1.5 cm.

Main fabric:

1. Back - cut 2
2. Upper left front - cut 1
3. Upper right front - cut 1
4. Lower left front - cut 1
5. Lower right front - cut 1
6. Front neck facing - cut 1
7. Back neck facing - cut 2



8. Upper sleeve – cut 2

Main fabric 1:

1. Lower sleeve – cut 2
2. Placket left – cut 1
3. Placket right – cut 1

Fusible interfacing:

1. Front neck facing – cut 1
2. Back neck facing – cut 2

INSTRUCTIONS:

1. Apply interfacing to facings.
2. Sew waist darts on back, press bulk towards center.
3. Serge separately center back edges. Sew center back seam from notch for zipper to bottom, press seam apart, pressing the slit for zipper at the same time. Sew in zipper.
4. Sew darts on upper pieces of dress. Press bulk towards top. Sew left upper piece to right upper piece. Press towards the left part and serge. Sew a decorative stitch along the seam at 0.5 cm.
5. Fold the right placket lengthwise, right sides together and sew lower edge. Trim corner. Placket turn right side out, press lower edge and the fold. Sew a decorative stitch, with a thread in the color of the main fabric at 0.5 cm. Sew placket to the lower right part of dress. Serge and press towards lower part of dress. Finish the left lower part in a similar way. Pin the right lower placket onto the left lower placket, right sides up, and baste together along the upper edge.
6. Sew lower parts of dress to upper parts. Serge and press towards top. Sew a decorative stitch along the seam at 0.5 cm.
7. Sew side and shoulder seams, press seams towards back and serge.
8. Sew shoulder seams of neck facings, serge outer edge. Pin facing to garment right sides together and sew the neckline. Clip into curves, turn facing under, straighten and press. Slipstitch facing to shoulder seams and to zipper tape.
9. Sew upper sleeve to lower sleeve. Serge and press towards top. Sew a decorative stitch,

with a thread in the main fabric color at 0.5 from seam. Sew sleeve seam, serge, and press. Sew sleeves into armholes, matching notches. Serge and press.

10. Serge hem of garment and lower edge of sleeve, press onto wrong side and topstitch

Congratulations, your dress is ready! :)