

If the pattern has a double line around it, the seam allowances are included.

**Note:** By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

**Important!** Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

## 2506 Denim jacket with trim

Recommendations on fabric: natural/mixed jeans fabrics, contrasting fabric for decoration.

You will also need: fusible interfacing; 4 buttons.



### CUTTING:

The word, "beam" used on some patterns means "straight of grain". Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Seam allowances: all seams 1 cm. Seam allowance for hem of garment – 2.5 cm.

### Main fabric:

1. Center back – cut 2
2. Side back – cut 2
3. Side front – cut 2
4. Upper front – cut 2
5. Center front – cut 2
6. Upper sleeve – cut 2
7. Lower sleeve – cut 2
8. Cuff – cut 2
9. Center front facing – cut 2
10. Lapel – cut 4
11. Stand collar – cut 2

12. Back neck facing – cut 1

Decorative fabric:

1. Front inset – cut 2

Fusible interfacing:

1. Center front facing – cut 2

2. Lapel – cut 2

3. Back neck facing – cut 1

INSTRUCTIONS:

1. Apply fusible interfacing.

2. Sew side backs to center back, press towards center, serge and topstitch at 0.5 cm from seam. Sew center back seam, press towards left, serge and topstitch at 0.5 cm from seam.

3. Sew upper front to side front, press towards top, serge and topstitch at 0.5 cm from seam. Sew side fronts to front, press towards center, serge and topstitch at 0.5 cm from seam.

4. Sew front inset to garment to front, clipping into seam allowance near corner. Press seam allowances towards inset, serge.

5. Sew shoulder and side seams, press seam allowances towards back and serge.

6. Pin lapels together, right sides together and sew outer edge. Clip seam allowances, turn the lapels right side out, straighten and press. Pin stand collars together right sides together and sew outer edge. Clip seam allowances, turn stand collar right side out, straighten and press.

7. Pin lapels onto center front and topstitch at neckline edge. Sew the stand collar into neckline.

8. Sew shoulder edges of center front facings and back neckline facing, press seam apart. Serge outer edge. Pin center front facing onto main piece, right sides together, pin together and sew button stand, front neckline, back neckline, and lower edge. When stitching makes sure to place the front piece on top. Topstitch seam allowance on button stand onto button stand. Place stitch line at 0,2 cm from seam. Turn center front facing onto wrong side, straighten, press. Baste to the main piece along the shoulder edges.

9. Sew the elbow edges of the sleeve separately. Sew the elbow seam of sleeve from the cap to the mark, clip into seam allowance near the notch. Press the seam allowance on the area from sleeve cap to mark and sew a decorative stitch along the seam at 0.5 cm. Press apart the seam allowances on the area from the mark down to hem and sew decorative stitch along the edges at 0.1 cm. Sew front seam on sleeve, press seam allowances towards lower part and serge. Sew sleeves into armholes matching notches, serge, and press.

10. Fold cuffs in half lengthwise right sides together and sew short sides. Start and stop stitching exactly at the marked line of the cuff seam. Turn cuff right side out, straighten and press. Sew outer side of cuff to lower edge of sleeve, press towards cuff. Fold the seam allowance of the inner side onto the wrong side and press and stitch in the ditch.

11. Make buttonholes on right front, sew on buttons on left front. Make buttonholes and sew on buttons onto cuffs.

Congratulations, your jacket is ready! :)