

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

Important! Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

2548 Blouson with shaped collar

Recommendations on fabric: natural/mixed knit fabric of small stretchiness.

You will also need: knit fusible interfacing; 3 buttons.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Seam allowances: seam allowance for hem of garment and hem of sleeve – 2 cm, other seams - 1.0 cm.

Main fabric:

1. Back – cut 1 on fold
2. Center front – cut 2
3. Side front – cut 2
4. Front yoke – cut 2
5. Sleeve – cut 2
6. Collar – cut 2

Fusible interfacing:

1. Collar – cut 1

INSTRUCTIONS:

1. Apply fusible interfacing.
2. Sew yoke to the side front, press seam allowances at yoke, serge.
3. Sew side fronts to front, press towards center, serge. Sew the center front seam, press seam allowances towards left, serge.
4. Sew shoulder seams, press seams towards back and serge.
5. Pin together collars right sides together and sew the outer edge and the right side up to the mark. Clip into seam allowance near the notch, trim away corner, turn collar right side out, straighten and press. Pin right collar onto left collar, matching the marks for center front, and baste together along lower edge. Sew collar into neckline, press towards top and serge.
6. Sew side seams, press seams towards back and serge.
7. Sew sleeve seam, serge, and press. Sew sleeves into armholes, serge, and press.
8. Serge the hem of garment and lower edge of sleeve, press onto wrong side and topstitch.
9. Sew buttons onto collar, while fixing the right side of the collar to the garment with the buttons.

Congratulations, your blouson is ready! :)