

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

Important! Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

2563 Blouse with V-neckline back

Recommendations on fabric: natural/mixed fabrics suitable for blouses.

You will also need: fusible interfacing, 5 buttons.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Seam allowances: all seams 1 cm. Seam allowance along upper edge of pocket – 2 cm.
Seam allowance for hem of garment – 1.5 cm.

Main fabric:

1. Back – cut 1 on fold
2. Front – cut 2
3. Cuff – cut 2
4. Back yoke – cut 2
5. Center front facing - cut 2

Fusible interfacing:

1. Cuff – cut 2
2. Center front facing – cut 2

INSTRUCTIONS:

1. Apply fusible interfacing.
2. Make and baste a box pleat on the back piece.
3. Serge the upper edge of pocket, seam allowance fold inside and topstitch. Fold under the seam allowances of pocket and press. Pin the pocket onto the left front and topstitch.
4. Sew shoulder seams, press towards the back, serge.
5. Serge the outer edge of the center front facing. Pin center front facing onto front and neckline yokes and sew. Clip seam allowances, fold the central front facing towards wrong side and press. Pin the left back neckline onto the right back neckline and sew together by hand in the center.
6. Sew back yoke to yoke, press seam allowances down and serge.
7. Sew side seams, press towards the back, serge.
8. Sew cuff into a ring, press the seam apart. Fold cuff in half lengthwise right side out and press. Sew the outer edge of cuff to armhole, fold inside the seam allowance of inner cuff and stitch-in-the ditch into seam of outer cuff.
9. Serge the lower edge of garment, press onto wrong side and topstitch.
10. Make buttonholes on the right front. Sew on buttons onto the left front.

Congratulations, your blouse is ready! :)