

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

Important! Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

2567 Light coat-cardigan without closure

Recommendations on fabric: natural/mixed fabric suitable for coats. Knit fabric in two matching or contrasting colors.

You will also need: fusible interfacing.

CUTTING:

The word, "beam" used on some patterns means "straight of grain". Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Seam allowances: all seams 1 cm. Seam allowance along hem of garment – 3 cm.

Main fabric:

1. Back – cut 1 on fold
2. Front – cut 2
3. Sleeve – cut 2

Main fabric 1:

1. Cuff – cut 2

Main fabric 2:

1. Collar – cut 1 on fold



INSTRUCTIONS:

1. Apply fusible interfacing to the one-piece center front facing.
2. Serge the center edges of fronts.
3. Sew shoulder seams. Serge seams and press towards back.
4. Fold the collar half lengthwise, wrong sides together, and sew it into neckline. Serge the seam allowances.
5. Clip into seam allowance in the corner on front, wrap the lower edge of collar with one-piece center front facing and sew along the horizontal edge. Fold the central front facing towards the wrong side and press the center front edges.
6. Sew in sleeves. Serge the seam allowances and press onto sleeve. Sew side seams and sleeve seams. Serge seams and press towards back.
7. Make and baste pleats on sleeves. Sew cuff into ring. Fold cuff in half lengthwise and press. Sew cuff to sleeve, serge.
8. Serge the seam allowance along the hem, turn inside and topstitch.

Congratulations, your coat-cardigan is ready! :)