

If the pattern has a double line around it, the seam allowances are included.

**Note:** By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

**Important!** Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

## 2573 Voluminous sweatshirt

Recommendations on fabric: neoprene, natural/mixed knit fabric of small stretchiness. Knit fabric in two matching or contrasting colors.

You will also need: separating zipper.



### CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Seam allowances: all seams 1 cm. Seam allowance along hem of garment – 1.5 cm.

### Main fabric:

1. Back – cut 1 on fold
2. Front – cut 2
3. Sleeve – cut 2

### Fabric 1:

1. Cuff – cut 2

### Fabric 2:

1. Stand collar – cut 1 on fold

## INSTRUCTIONS:

1. Serge the center edges of fronts. Sew the separating zipper to the center front edges.
2. Sew shoulder seams. Serge seams and press towards back.
3. Stand collar pin together half lengthwise right side out and sew into neckline. Clip into seam allowance in the corner on front, sew along the horizontal edge. Serge the seam allowances.
4. Sew in sleeves. Serge the seam allowances and press onto sleeve. Sew side seams and sleeve seams. Serge seams and press towards back.
5. Make and baste pleats on sleeve. Sew cuff into ring. Fold cuff in half lengthwise and press. Sew cuff to sleeve, serge.
6. Make and stitch box pleats on front and on back. Baste the pleats by hand at the lower edge to fix them. Serge the seam allowance along the hem, turn inside and topstitch.

Congratulations, your sweatshirt is ready! :)