

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

Important! Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

2619 Sweater with Deep V-Neckline

Recommendations on fabric: soft natural/mixed knit fabric of medium stretchiness.

CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.



Seam allowances: all seams 1 cm.

Main fabric:

1. Back – cut 1 on fold
2. Inner front – cut 1 on fold
3. Outer front – cut 2
4. Front placket – cut 2
5. Sleeve – cut 2
6. Hem placket – cut 1 on fold
7. Cuff – cut 2
8. Back neck facing – cut 1

INSTRUCTIONS:

Advice: sew knit pieces with special elastic/zig-zag stitches. If you use an overlock, cut

seam allowances to 0.6-0.8 cm width. Topstitch hem allowances with double needle to save elasticity.

1. Serge the upper seam allowance of the inner front piece. Turn it to the wrong side and topstitch with two parallel stitch lines to prevent stretching.
2. Fold the front placket in half lengthwise, right side out, and sew it to the outer front piece. Press the seam allowance toward the main piece and serge.
3. Place the right front over the left front and baste the plackets together along the lower edge. Pin the outer front to the inner front and baste together along the armhole edges, side seams, and lower edge.
4. Serge the outer edge of the back neckline facing. Pin the neckline facing to the back and sew the neckline exactly to the marked shoulder seam line. Clip the seam allowances, turn the facing to the wrong side, and press.
5. Sew the shoulder seams, placing the front between the back and the facing. Press the seam allowances toward the back and serge.
6. Sew the side seams. Press the seam allowances toward the back and serge.
7. Sew the hem band into a ring and press the seam allowances open. Fold the band in half lengthwise, right side out, and sew it to the lower edge of the garment. Press the seam allowances upward and serge.
8. Sew the sleeve seams. Press the seam allowances toward the back and serge. Set the sleeves into the armholes, matching the notches. Serge the seam allowances and press.
9. Sew the cuffs into rings and press the seam allowances open. Fold each cuff in half lengthwise, right side out, and sew it to the sleeve. Serge the seam allowances and press them toward the sleeve.

Congratulations – your sweater are finished! :)