

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

Important! Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

2638 Skirt with Yoke and Gathers

Recommendations on fabric: thin natural/mixed suiting fabrics.

You will also need: fusible interfacing; 1 button; dress zipper.

CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.



Seam allowances: all seams – 1 cm. . Seam allowance along the lower edges – 2 cm.

Main fabric:

1. Back yoke – cut 1
2. Back – cut 2
3. Front skirt – cut 2
4. Front yoke – cut 1
5. Belt – cut 1

Fusible interfacing:

1. Belt – cut 1

INSTRUCTIONS:

1. Apply fusible interfacing.
2. Sew the center seam of the back skirt. Press the seam allowances toward the left and serge.
3. Sew a gathering stitch along the upper edge of the back skirt and gather the fullness. Sew the yoke to the back skirt. Press the seam allowances upward and serge. Sew a decorative topstitch 0.5 cm from the seam.
4. Sew the center seam of the front skirt. Press the seam allowances toward the left and serge.
5. Sew a gathering stitch along the upper edge of the front skirt and gather the fullness. Sew the yoke to the front skirt. Press the seam allowances upward and serge. Sew a decorative topstitch 0.5 cm from the seam.
6. Serge the left side edges separately. Sew the left side seam from the zipper notch to the hem. Press the seam allowances open and insert the zipper. Sew the right side seam. Press the seam allowances toward the back and serge.
7. Fold the belt in half lengthwise, right sides together, and sew the short edge and corner. Start stitching exactly at the marked seam line between the belt and skirt. Clip into the seam allowances near the marking, turn the belt right side out, and press. Sew the outer edge of the belt to the upper edge of the skirt. Fold the inner edge under and stitch in the ditch.
8. Serge the hem allowance, press it to the wrong side, and topstitch.
9. Make a buttonhole on the belt. Sew on the button.

Congratulations – your skirt are finished! :)