

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

Important! Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

2661 Skirt with Front Draping

Recommendations on fabric: thick natural/mixed fabrics suitable for skirts.

You will also need: fusible interfacing; 4 decorative buttons; 1 button at belt; dress zipper.

CUTTING:

The word, "beam" used on some patterns means "straight of grain". Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.



Seam allowances: all seams – 1 cm. Seam allowance along hem 2 cm. Seam allowance along the shaped edge of the fly piece – 1.5 cm.

Main fabric:

1. Front skirt – cut 1
2. Back – cut 1 on fold
3. Fly piece – cut 1
4. Belt – cut 1

Fusible interfacing:

1. Belt – cut 1

INSTRUCTIONS:

1. Apply fusible interfacing to the belt.
2. Serge the center and lower seam allowances of the overlay piece. Fold the seam allowances to the wrong side and topstitch. Pin the overlay piece to the front skirt with the right sides of both pieces facing upward. Baste them together along the side and upper edges.
3. Serge the left side edges separately. Sew the left side seam from the zipper marking to the hem. Press the seam allowances open and insert the zipper.
4. Sew the right side seam. Serge the seam allowances and press them toward the back.
5. Sew the outer edge of the belt to the upper edge of the skirt. Sew the belt ends, trim the corners, and turn the belt right side out. Fold the inner edge of the belt under and stitch in the ditch. Press the belt.
6. Sew the decorative buttons through both the overlay piece and the front skirt, matching the notches and securing all layers together.
7. Mark and make the buttonhole on the belt. Sew on the button.
8. Serge the skirt hem, press it to the wrong side, and topstitch.

Congratulations – your skirt are finished! :)