

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

Important! Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

2676 Skirt with Yoke and Belt

Recommendations on fabric: thin natural/mixed suiting fabrics.

You will also need: lining; fusible interfacing; 1 button; dress zipper; buckle; grommets.

CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Seam allowances: all seams – 1 cm. Seam allowance along the lower edges – 2 cm.

Main fabric:

1. Back skirt yoke – cut 2
2. Back – cut 2
3. Front skirt yoke – cut 2
4. Front skirt – cut 2
5. Belt – cut 1
6. Pocket welt – cut 2
7. Decorative belt – cut 1 on fold
8. Belt Loop – cut 1



Lining:

1. Large pocket bag – cut 2
2. Small pocket bag – cut 2

Fusible interfacing:

1. Belt – cut 1
2. Pocket welt – cut 2
3. Decorative belt – cut 1 on fold

INSTRUCTIONS:

1. Apply fusible interfacing.
2. Sew the yoke to the back skirt. Press the seam allowances upward and serge. Sew two decorative topstitching lines along the seam, 0.1 cm and 0.7 cm from the seam. Sew the center back seam. Press the seam allowances toward the left and serge. Sew two decorative topstitching lines along the seam, 0.1 cm and 0.7 cm from the seam.
3. Mark the pocket positions on the front skirt yokes. Fold each welt in half lengthwise, wrong sides together, and press. Topstitch the small pocket bag to the inner side of the welt. Sew the pocket welt to the yoke along the lower pocket marking line. Sew the larger pocket bag to the yoke along the upper pocket marking line. Stop stitching at the short pocket marking lines. Cut the pocket opening and clip diagonally toward the ends of the stitching, stopping 1–1.5 cm from each end. Turn the welt and large pocket bag to the wrong side through the opening. Secure the pocket ends with double backstitching near the corners. Sew the pocket bag edges together and serge.
4. Sew the front skirt to the yoke. Press the seam allowances upward and serge. Sew two decorative topstitching lines along the seam, 0.1 cm and 0.7 cm from the seam. Sew the center front seam. Press the seam allowances toward the left and serge. Sew two decorative topstitching lines along the seam, 0.1 cm and 0.7 cm from the seam.
5. Serge the left side edges separately. Sew the left side seam from the zipper notch to the hem. Press the seam allowances open and insert the zipper. Sew the right side seam. Press the seam allowances toward the back and serge.
6. Fold the belt loop strip in half lengthwise, right sides together, and sew along the long edge. Turn it right side out, position the seam along the fold, and press. Cut the strip into belt loops and mark their positions. Sew the belt loops to the upper edge of the skirt according to the markings and over the side seams.
7. Fold the waistband in half lengthwise, right sides together, and sew the short edge and corner. Start stitching exactly at the marked seam line between the waistband and skirt. Clip into the seam allowances near the marking, turn the waistband right side out, and press. Sew the outer edge of the waistband to the upper edge of the skirt. Fold the inner edge under and stitch in the ditch. Topstitch the belt loops to the

upper edge of the waistband.

8. Serge the hem allowance, press it to the wrong side, and topstitch.
9. Make a buttonhole in the waistband and sew on the button.
10. Fold the decorative belt in half lengthwise, right sides together, and sew one long edge and one short edge. Trim the corners, turn the belt right side out, and press. Serge the remaining short edge. Sew decorative topstitching around all edges, 0.1 cm and 0.7 cm from the edge. Attach the buckle to the belt end. Install the grommets.

Congratulations – your skirt are finished! :)