

If the pattern has a double line around it, the seam allowances are included.

**Note:** By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

**Important!** Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

## 2744 Blouson with deep V-neck and collar

Recommendations on fabric: natural/mixed fabrics suitable for blouses approx. 1 m (size 32-42), approx. 1.3 m (size 44-54) with a fabric width of 150 cm.

You will also need: fusible interfacing, 1 button.



### CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Seam allowances: all seams 1 cm. Seam allowance along the lower edge of the garment – 3 cm.

### Main fabric:

1. Back - cut 1 on fold
2. Front – cut 2
3. Sleeve – cut 2
4. Cuff – cut 2
5. Collar – cut 2
6. Center front facing – cut 2
7. Button loop – cut 1

### Fusible interfacing:

1. Center front facing – cut 2

2. Button loop – cut 1
3. Cuff – cut 2
4. Collar - cut 1

#### INSTRUCTIONS:

1. Apply fusible interfacing.
2. Sew the front darts and press the bulk towards the top.
3. Fold the button loop in half lengthwise with the right sides together, and sew along the longer and one shorter side. Turn the piece right side out, straighten, and press.
4. Snip into seam allowances on the fronts near the mark for the neckline slit. Sew the center front seam, press the seam open, and serge. Snip into seam allowances on the center front facings near the mark for the neckline slit. Sew the center seam of the center front facings, press the seam open, and serge. Serge the outer edge.
5. Pin the center front facings onto the front, right sides together, and sew along the neckline, inserting the button loop on the right side according to the markings. Press the seam, turn the center front facings to the wrong side, straighten, and press. Topstitch the center front facings onto the front 0.5 cm from the outer edges.
6. Sew the side and shoulder seams, press towards the back, and serge.
7. Pin the collars together, right sides facing, and sew the ends and collar fall. Start and stop stitching exactly at the marked collar seam. Clip the seam allowances, trim the corners, turn the collar right side out, straighten, and press. Sew the upper collar into the neckline, fold the seam allowance of the lower collar inside, and topstitch along the seam.
8. Sew the sleeve seam, press towards the back, and serge. Sew the sleeves into the armholes, serge, and press.
9. Sew the cuff into a ring, press the seam open. Fold the cuff in half lengthwise and press with the right side out. Sew the cuff to the sleeve from the wrong side and serge. Fold the cuff to the right side, press, and hand-sew the cuff to the sleeve.
10. Serge the lower edge, press to the wrong side, and topstitch.
11. Sew a button on the left side of the slit on the front.

Congratulations, your blouson is ready! :)



Model 2744

pattern from pppp.dk