

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

Important! Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

2746 Blouse with stand-up collar and pleats at the neck

Recommendations on fabric: natural/mixed fabrics suitable for blouses.

You will also need: fusible interfacing; 8 buttons.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Seam allowances: seam allowance for hem of garment – 2.0 cm, other seams 1 cm.

Main fabric:

1. Back – cut 1 on fold
2. Yoke – cut 1 on fold
3. Front – cut 2
4. Stand collar – cut 2
5. Center front facing – cut 2
6. Sleeve – cut 2
7. Cuff – cut 2

Fusible interfacing:

1. Stand collar – cut 1
2. Center front facing – cut 2

3. Cuff – cut 2

INSTRUCTIONS:

1. Apply fusible interfacing.
2. Make and baste pleats on the fronts, folding the bulk towards the side. Pin the center front facing to the front with right sides together and sew the center front edge. Clip the seam allowances, turn the center front facing to the wrong side, straighten, and press.
3. Sew the outer stand collar to the neckline yokes, clip the seam allowances, and press towards the stand collar. Fold under the seam allowance of the inner stand collar and press. Pin the stand collars together with right sides facing and sew the upper edge, starting and stopping precisely at the marked line of the side edge.
4. Sew the shoulder seams, inserting the front between the back and the inner stand collar. Press the seams towards the back and serge. Turn the stand collar right side out and topstitch the inner stand collar into the seam between the outer stand collar and the main piece.
5. Sew the yoke to the back, press the seam allowances upwards, and serge.
6. Sew the side seams, press the seam allowances towards the back, and serge.
7. Serge the sleeve edges separately. Sew the sleeve seam from the armhole up to the mark for the slit, then press the seam open. Topstitch the slit 0.1 cm from the fold. Sew the sleeves into the armholes, serge, and press.
8. Fold the cuffs in half lengthwise with right sides together and sew the side edges, starting and stopping precisely at the marked line of the cuff seam. Turn the piece right side out and press. Sew the outer part of the cuff to the sleeve, fold the inner side of the cuff inside, and topstitch it into the seam of the outer cuff.
9. Serge the lower edge of the garment, fold it to the wrong side, and topstitch.
10. Make buttonholes on the right front and sew buttons on the left front. Make buttonholes and sew buttons onto the cuffs.

Congratulations, your blouse is ready! :)