

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

Important! Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

2805 Light Summer Jacket with Notched Collar

Recommendations on fabric: natural/mixed suiting fabrics.

You will also need: fusible interfacing; two buttons.

CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.



Seam allowances: all seams 1 cm. Seam allowance along the lower edge of the garment – 2.5 cm.

Main fabric:

1. Back – cut 1 on fold
2. Back yoke – cut 1
3. Front – cut 2
4. Sleeve – cut 2
5. Cuff – cut 2
6. Center front facing – cut 2
7. Back neck facing – cut 1
8. Decorative Tab – cut 2

Fusible interfacing:

1. Cuff – cut 2
2. Center front facing – cut 2
3. Back neck facing – cut 1

INSTRUCTIONS:

1. Apply fusible interfacing.
2. Sew yoke to back. Serge seams and press towards the top.
3. Sew center edge of one-piece collar. Clip into the seam allowance of the shoulder seam at the corner. Sew shoulder seams, sewing the collar into the neckline at the same time. Clip seam allowances and press.
4. Sew the center collar edge to center front facings. Press the seam allowances apart. Sew shoulder seams of facings and center front facings, sewing the collar into the neckline at the same time. Serge the outer edge. Pin center front facing to garment, right sides together, and sew along the center front edge and collar. Clip seam allowances, trim corners, fold facings to the wrong side, and press.
5. Fold decorative tabs in half lengthwise, right sides together, and sew along the longer and one shorter edge. Turn right side out, trim seam allowances in corners, straighten, and press. Serge the unfinished shorter edge. Make a buttonhole on each tab. Topstitch decorative tabs according to markings onto the wrong side of the sleeves.
6. Sew sleeves into armholes. Serge seam allowances and press towards sleeves.
7. Sew side seams, sewing sleeve edges at the same time. Serge seams and press towards the back.
8. Sew cuff into a ring. Fold cuff in half lengthwise, right side out, and press. Sew the outer part of the cuff to the sleeve. Fold under the seam allowance of the inner side of the cuff and topstitch in the ditch along the seam of the outer cuff.
9. Serge the lower edge of the garment. Press to the wrong side and topstitch.
10. Make buttonholes on decorative tabs. Sew on buttons on sleeves.

Congratulations, your jacket is ready! :)