

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

Important! Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

2817 Blouse with Long Shirt Collar

Recommendations on fabric: natural/mixed fabrics suitable for blouses with elastane, silk.

You will also need: fusible interfacing; 9 buttons.

CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.



Seam allowances: 1 cm for all seams.

Main fabric:

1. Back – cut 1 on fold
2. Front – cut 2
3. Sleeve – cut 2
4. Center front facing – cut 2
5. Collar – cut 2
6. Stand collar – cut 2
7. Cuff – cut 2

Fusible interfacing:

1. Center front facing – cut 2
2. Collar – cut 1
3. Stand collar – cut 1
4. Cuff – cut 2

INSTRUCTIONS:

1. Apply fusible interfacing.
2. Make and baste pleats on the shoulder edge of the front. Press bulk towards the center.
3. Pin the center front facing to the front, right sides together, and sew the center front edge and neckline edge. Clip seam allowances, turn the facings to the wrong side, straighten, and press.
4. Sew shoulder seams, leaving the shoulder seam allowance on the back protruding by 1 cm. Press seams toward the back and serge.
5. Sew side seams. Serge seams and press toward the back.
6. Pin the collar pieces together, right sides facing, and sew the ends and outer edge. Trim corners, turn the collar right side out, straighten, and press. Pin the stand collar pieces together, right sides facing, inserting the prepared collar between them, and sew, stitching the ends of the stand collar at the same time. Turn the finished collar right side out and press. Sew the outer stand collar to the back neckline. Fold under the seam allowance of the inner stand collar and stitch in the ditch. Fold inside the unfinished seam allowance of the stand collar and sew together.
7. Serge the sleeve edges separately. Sew the sleeve seam from the top down to the slit mark. Press seam allowances open. Sew a fastening stitch along the slit at 0.3 cm from the edge. Sew sleeves into the armholes, serge, and press. Sew a gathering stitch along the lower edge of the sleeve and gather fullness.
8. Fold the cuff in half lengthwise, right sides together, and sew the short sides. Turn the cuff right side out, straighten, and press. Sew the outer side of the cuff to the sleeve, fold inside the seam allowance of the inner cuff, and topstitch into the seam of the outer cuff.
9. Serge the lower edge of the garment. Press the seam allowance to the wrong side and topstitch.
10. Make buttonholes and sew on buttons on the front and cuffs. Make a buttonhole and sew on a button at the stand collar.

Congratulations – your blouse are finished! :)