

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

Important! Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

2828 Long Tunic Dress with Side Slits

Recommendations on fabric: soft natural/mixed knit fabric of medium stretchiness.

CUTTING:

The word, "beam" used on some patterns means "straight of grain". Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Seam allowances: all seams – 1 cm. Seam allowance for hem of garment and hem of sleeve – 2 cm. Seam allowance along the side slits of the back and front – 2 cm

Main fabric:

1. Back – cut 1 on fold
2. Front – cut 1 on fold
3. Sleeve – cut 2
4. Collar – cut 1

INSTRUCTIONS:

Advice: sew knit pieces with special elastic/zig-zag stitches. If you use an overlock, cut seam allowances to 0.6-0.8 cm width. Topstitch hem allowances with double needle to save elasticity.



1. Sew shoulder seams, press towards the back, and serge.
2. Serge side edges separately. Sew side seams from armhole to notch, press the seam apart, and also press the slits. Place a finishing and securing stitch along the edge of the slit, 0.5 cm from the edge.
3. Sew collar into a ring, fold in half lengthwise, and sew into neckline, slightly stretching it. Position the seam near the left shoulder seam. Serge the seam allowances and press towards the main piece.
4. Sew sleeve seam, press towards the back, and serge. Sew sleeves into armholes, matching notches. Serge and press.
5. Serge hem allowance and sleeve hem, fold inside onto wrong side, and topstitch.
6. Cut 4 bias tapes for ties, each 4 cm wide and twice the waist circumference in length. Fold the tape in half lengthwise, wrong sides together, and press. Unfold and press the long sides inward to meet at the center line. Fold in half again and stitch along the edge to secure.
7. Place one short end of the tie under the slit at the waist mark on the back and front, and topstitch. Fold the loose ends under and topstitch, or finish with decorative end caps.

Congratulations – your tunic dress are finished! :)