

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

Important! Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

4070 Blouse with Stand Collar and Gathers

Recommendations on fabric: natural/mixed medium to high stretchy fabric.

CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.



Seam allowances: hem allowance, sleeve hem – 1.5 cm, all other seams – 0.8 cm.

Main fabric:

1. Upper front – cut 1
2. Lower center front – cut 1
3. Lower side front – cut 2
4. Back – cut 1
5. Side back – cut 2
6. Collar – cut 1
7. Front sleeve – cut 2
8. Back sleeve – cut 2

INSTRUCTIONS:

Advice: sew knit pieces with special elastic/zig-zag stitches. If you use an overlock, cut seam allowances to 0.6-0.8 cm width. Topstitch hem allowances with double needle to save elasticity.

1. Sew center back to side backs. Sew side fronts to lower front. Serge seams and press towards center.
2. Sew a gathering stitch along the lower edge of upper front between triangle marks. Gather fullness. Sew upper front to lower front. Serge seam and press downwards.
3. Sew shoulder seams. Serge and press towards back.
4. Sew elbow seam of sleeve. Serge and press towards back. Sew sleeve into open armhole, matching notches. Serge seam allowance.
5. Sew side seam and sleeve seam in one step. Serge and press towards back.
6. Fold collar into a ring right sides together and sew. Turn collar right side out, fold in half wrong sides together. Sew collar into neckline, matching notches. The collar seam should be near the left shoulder seam. Serge and press collar seam.
7. Serge hems, fold to wrong side and topstitch.

Congratulations – your blouse are finished! :)