

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

Important! Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

4093 Tunic with Cowl Neckline

Recommendations on fabric: natural / mixed, medium to high stretch-knit fabric.

CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Seam allowances: on hem and edge of sleeve – 1.5 cm, all other seams 0.7 cm.

Main fabric:

1. Back – cut 1 on fold
2. Front – cut 1 on fold
3. Sleeve – cut 2
4. Collar – cut 1

INSTRUCTIONS:

Advice: sew knit pieces with special elastic/zig-zag stitches. If you use an overlock, cut seam allowances to 0.6-0.8 cm width. Topstitch hem allowances with double needle to save



elasticity.

1. Sew darts on the front, pressing towards the hem.
2. Make soft pleats along the front neckline according to the markers. Press pleats towards the side edge and baste in place.
3. Sew shoulder seams. Serge and press seams towards the back.
4. Sew collar into a ring and press seam allowances open. Sew the inner edge of the collar into the neckline, matching notches and stretching the edge of the collar slightly. Position the collar seam near the left shoulder seam. Press the collar joining seam.
5. Sew sleeves into open armholes, matching notches. Serge and press seam allowances.
6. Sew side seams, stitching sleeve seams at the same time. Serge and press seam allowances towards the back.
7. Serge the bottom edge of the garment, lower edge of sleeves, and outer edge of the collar. Turn to the wrong side, press, and topstitch.

Congratulations – your tunic are finished! :)