

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

Important! Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

4119 Top with waterfall front

Recommended fabric: knit fabric, jersey, stretch fabric of medium or high stretchiness.

Seam allowance: 1 cm on all edges. Neckline and armholes – 1.5 cm.

CUTTING:



The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Advice: Knit fabric pieces are sewn together with special elastic or narrow zig-zag stitch. Seam allowance on hem is stitched with twin needles to save stretchiness. Pieces can also be sewn together with 3 or 4 – thread serger. Cut the seam allowance to 0.6 - 0.8 cm when serge the seams.

Main fabric:

1. Back – cut 1 on fold
2. Front – cut 1 on fold
3. Bottom – cut 1 on fold

INSTRUCTIONS:

1. Sew side and shoulder seams. Serge and press toward back.

2. Serge neckline, fold to wrong side and topstitch.
3. Serge armhole, fold to wrong side and topstitch.
4. Sew bottom part into ring. Fold in half lengthwise, wrong sides together, and sew to hem, stretching a little bit. The seam is at the left side seam. Serge the seam.

Congratulations, your top is ready! :)