

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

Important! Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

4139 Chiffon Tunic with Smocking

Recommendations on fabric: light-weight natural/mixed blouse fabrics.

You will also need: elastic thread; 2 buttons; bias tape.

CUTTING:

The word, "beam" used on some patterns means "straight of grain". Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Seam allowances: all seams 1 cm, on hem – 4 cm.

Main fabric:

1. Front – cut 2
2. Back – cut 2
3. Cuff – cut 2

INSTRUCTIONS:

1. Sew the right shoulder seam. Serge and press toward the back.
2. Cut bias tape equal in length to the neckline and 4 cm wide. Fold it in half lengthwise and press. Pin the bias tape to the neckline edge, right sides together, and sew. Turn the bias tape to the wrong side and topstitch 0.1 cm from the fold.



3. Sew the left shoulder seam. Serge and press toward the back.
4. Serge the side and sleeve edges separately. Sew the side and sleeve seam, stopping at the sleeve opening mark. Press the seam open.
5. Topstitch along the sleeve slit, 0.1 cm from the edge. Fold the cuffs in half, right sides together, and sew the short sides and overlap edge according to the markings. Trim the seam allowances at the corners. Turn the cuffs right side out and press. Sew the outer edge of the cuff to the sleeve. Fold the inner cuff seam allowance under and topstitch into the joining seam.
6. Serge the lower edge of the garment, turn it to the wrong side, and topstitch. Sew rows of stitching with elastic thread according to the markings.
7. Make buttonholes on the cuffs and sew on the buttons.

Congratulations – your tunic are finished! :)