

If the pattern has a double line around it, the seam allowances are included.

**Note:** By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

**Important!** Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

## 4179 Double-sided coat

Recommendations on fabric: natural or mixed fabrics suitable for coats of contrast colors

You will also need: fusible interfacing; lining; raglan shoulder pads; 1 button; 1 inner button

### CUTTING:

The word, "beam" used on some patterns means "straight of grain". Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.



### Main fabric:

1. Back part – 1 detail
2. Central front part – 2 details
3. Side front part – 2 details
4. Collar – 1 detail
5. Sleeve – 2 details
6. Belt – 1 detail

### Decoration fabric:

1. Collar – 1 detail
2. Buttonstand – 2 details
3. Back neckline facing – 1 detail

4. Cuff – 2 details
5. Belt – 1 detail

Lining:

1. Back part – 1 detail
2. Central front part – 2 details
3. Side front part – 2 details
4. Sleeve – 2 details

ATTENTION: details of back part, front part and sleeve from lining are cut except for back part neckline facings, buttonstands and cuff correspondingly.

Fusible interfacing: buttonstand, back part neckline facing, collar, cuff

INSTRUCTIONS:

1. Apply fusible interfacing to buttonstand, back neckline facing, collar of decoration fabric, cuffs. Apply fusible interfacing to location of pocket on central and side front parts.
2. Sew darts on central front parts, press depths upwards.
3. Stitch pocket bags to one-piece underlay pieces. Press seams to pocket bag. Stitch side front parts to central parts, sewing pocket bags at the same time. Slash seams on side front part near pocket opening. Press underlay pieces towards center of front part, press princess seam apart and serge from hem up to the pocket.
3. Sew side and shoulder edges, press seam allowances apart. Serge seam allowances of side edges from hem up to waist.
4. Sew collar of main fabric into back part/ front part neckline. Press apart the seam.
5. Sew shoulder seams of back part neckline facing and buttonstand. Press seams apart. Sew collar of decoration fabric into the buttonstands/facing neckline. Press seam allowances apart.
6. Put buttonstand onto right side of front part right side downwards, pin together and overstitch along buttonstand, ends and outer edge of collar. Stitch lower edges of buttonstands to front part exactly along marked line of hem turnup, leaving 1.5 cm to inner edge of buttonstand. Cut seam allowances in corners. Turn bands onto right side, straighten seams. Serge lower edge of the garment and press onto wrong side.

7. Fold cuff with the sleeve right sides together and sew along the lower edge. Press seam allowances. Unfold the sleeve and cuff into one line and sew sleeve and cuff seam. Press apart the seam, turn cuff onto wrong side.
8. Sew sleeves into armholes according to notches. Sew in shoulder pads.
9. Sew and serge seams on lining details and sew in sleeves, similar to main fabric details.
10. Turn seam allowance of lower edge of lining twice and topstitch. Stitch lining to inner buttonstand edges and back part neckline facing. Start and finish the stitch on half of the width of hem turnup of the main garment. Fix allowances of collars connecting seams close to seams.
11. Stitch lining to inner edge of cuff. Turn coat onto right side. Sew hem of the coat with invisible stitches. Put decorative stitch at 0.7 cm off the edge of buttonstand, ends and outer edge of collar.
12. Make buttonhole on right front part, sew the button on left front part. Make buttonhole and sew the button on inner part.
13. Fold detail of the belt right sides together and overstitch, leaving a slit in long side. Turn belt onto right side, turn seam allowances of unsewn section inside and put decorative stitch at 0.7 cm off the edge along the perimeter of the belt.

Congratulations, your coat is ready! :)