

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

Important! Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

4328 Double-Breasted Jacket with Blazer Cut

Recommendations on fabric: suiting or coat fabrics of natural or mixed fibers.

You will also need: fusible interfacing; lining; 4 buttons; shoulder pads; sleeve heads.

CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.



Seam allowances: all seams – 1 cm, on hem of the garment and hem of sleeve – 3 cm.

Main fabric:

1. Center back – cut 2
2. Side back – cut 2
3. Side front – cut 2
4. Center front – cut 2
5. Buttonstand/facing (front band) – cut 2
6. Back neck facing – cut 1
7. Upper sleeve – cut 2

8. Lower sleeve – cut 2

Lining:

1. Center front – cut 2
2. Side front – cut 2
3. Center back– cut 2
4. Side back – cut 2
5. Upper sleeve – cut 2
6. Lower sleeve – cut 2

Attention! Front part and back part lining details are cut as using main pattern pieces except for the buttonstands/facing width and back neck facings accordingly.

Fusible Interfacing: center front, buttonstand/facing, back neck facing, garment hem and hem of sleeve.

INSTRUCTIONS:

1. Apply fusible interfacing.
2. On the center back, sew and press darts toward the center. On the center front, sew darts and press toward the hem. Sew side fronts to center fronts, clip into curves, and press toward the center. Sew side backs to backs, clip into curves, and press toward the center. Sew the center back seam and press it open.
3. Sew the front to the back at side seams. Press seams open. Sew shoulder seams, trim in the corner near the neckline, and press the seam open. Sew the center edge of the collar and press the seam open. Sew the collar into the neckline of the back and press the seam open.
4. Sew the back neck facing to the buttonstand/facing. Clip into corners. Sew the center edge of the collar and press the seam open. Sew the collar to the neck facing and press the seam open.
5. Place the buttonstand/facing onto the front, right sides together, pin and sew along the buttonstand/facing and outer collar edges. Understitch. Sew lower corners of the buttonstand. Trim seam allowances in the corners. Turn the buttonstand/facing to the inside, straighten the seams, and press. Press the garment hem.
6. Sew the elbow sleeve seam and press it open. Sew the front sleeve seam and press it open. Press the sleeve hem.

7. Sew a gathering stitch along the sleeve cap for ease. Sew sleeves into armholes according to notches, easing around the sleeve cap. Sew in shoulder pads and sleeve heads.
8. On lining pieces, sew seams and sew in sleeves, leaving an opening in the front right sleeve seam for turning. Press seams open.
9. Sew the lining to the inner buttonstand/facing edges and back neck facing. Tack seam allowances of the collar connecting seam close to the seams. Stitch the lining to the hem of the jacket and to the hem of the sleeve. Turn the jacket right side out through the opening in the sleeve. Slipstitch the opening closed.
10. Make buttonholes on both fronts according to the marks. On the left front, sew on a decorative button. On the right front, sew a decorative button from the right side, and an inner button from the wrong side.

Congratulations, your jacket is ready! :)