

If the pattern has a double line around it, the seam allowances are included.

**Note:** By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

**Important!** Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

## 4341 Hoodie with Asymmetrical Zipper

Recommendations on fabric: natural or mixed heavy, medium stretch knit fabric.

You will also need: zipper (length is shown on front pattern piece).

### CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Seam allowances: all seams 0.8 cm.

### Main fabric:

1. Back – cut 1
2. Right front – cut 1
3. Left front – cut 1
4. Lower front – cut 1
5. Sleeve – cut 2
6. Lower part (band) – cut 1 on fold
7. Cuff – cut 2



8. Front left of hood – cut 1, cut 1 for inner hood
9. Front right of hood – cut 1, cut 1 for inner hood
10. Back of hood – cut 2, cut 2 for inner hood

#### INSTRUCTIONS:

Advice: sew knit pieces with special elastic/zig-zag stitches. If you use an overlock, cut seam allowances to 0.6-0.8 cm width. Topstitch hem allowances with double needle to save elasticity.

1. Sew shoulder seams. Serge seams and press towards the back.
2. Sew the outer back part of the hood to the outer front and outer right parts of the hood. Serge seams. Make another hood for the lining and serge the lower edge. Sew the outer hood to the neckline. Serge the seam and press towards the hood.
3. Serge edges for the zipper. Sew in the zipper along the fronts and hood edge. Sew the inner hood to the outer hood, right sides together, along the upper edge. Clip into curves. Turn the inner hood to the inside. Fold under and slipstitch the inner center front seam allowance to the zipper tape. Topstitch the lower seam allowance of the inner hood into the neckline connecting seam. Topstitch the upper edge of the hood and along the zipper.
4. Sew the lower front to the upper parts. Serge the seam and press downwards. Topstitch.
5. Sew the sleeve into the open armhole, matching marks. Serge seam.
6. Sew the side seam and sleeve seam at the same time. Serge seam.
7. Sew the lower band into a ring. Press seam allowance apart. Fold in half, wrong sides together, and sew to the lower edge, slightly stretching the band. Serge seam and press upwards. Topstitch 0.5 cm from the seam.
8. Sew the cuff into a ring. Press seam allowance apart. Fold cuff in half, wrong sides together, and sew to the lower edge of the sleeve, slightly stretching the cuff. Serge seam and press towards the sleeve. Topstitch 0.5 cm from the seam.

Congratulations – your hoodie are finished! :)