

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

Important! Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

4343 Longsleeve with Draped Neckline

Recommendations on fabric: natural or mixed well-draping medium stretch knit fabric.

CUTTING:

The word, "beam" used on some patterns means "straight of grain". Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.



Seam allowances: on hem and along the edge of sleeve – 1.5 cm, seam allowance along neckline – 1.5 cm, all other seams – 0.8 cm.

Main fabric:

1. Back – cut 1
2. Front – cut 2
3. Sleeve – cut 2

INSTRUCTIONS:

Advice: sew knit pieces with special elastic/zig-zag stitches. If you use an overlock, cut seam allowances to 0.6-0.8 cm width. Topstitch hem allowances with double needle to save elasticity.

1. Sew shoulder and side neck seams. Serge seam allowances and press towards back.
2. Serge seam allowance of neckline, fold to the inside and topstitch.
3. Place right front over left front. Match side edges and baste with a temporary stitch 0.5 cm from the edge.
4. Sew sleeves into open armholes, serge seam allowances.
5. Sew side edges and sleeve edges at the same time. Serge seam allowances and press towards back.
6. Serge hem of garment and lower edge of sleeves. Fold under, press, and topstitch.

Congratulations – your long sleeve are finished! :)