

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

Important! Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

4385 Hooded Sweat Jacket

Recommendations on fabric: dense knit fabric.

You will also need: fusible interfacing, zipper (length is shown on front pattern piece), lining for pocket sackings.

CUTTING:

The word, "beam" used on some patterns means "straight of grain". Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Seam allowances: all seams 1 cm.

Main fabric:

1. Back – cut 1 on fold
2. Front – cut 2
3. Cuff – cut 2
4. Hood – cut
5. Lower placket – cut 1
6. Off-set welt – cut 2



Lining:

1. Big pocket sacking – cut 2
2. Small pocket sacking – cut 2

INSTRUCTIONS:

Advice: sew knit pieces with special elastic/zig-zag stitches. If you use an overlock, cut seam allowances to 0.6-0.8 cm width. Topstitch hem allowances with double needle to save elasticity.

1. Apply fusible interfacing to the off-set welts. Mark the pocket location. Apply interfacing to the pocket opening. Press the off-set welt in half lengthwise, wrong sides together. Topstitch the small pocket bag onto the inner side of the off-set welt.

Sew the off-set welt to the front along the lower line of the pocket marking. Sew the large pocket bag to the front along the upper line of the pocket marking. Stop stitching near the short marking lines. Cut the pocket opening. At 1–1.5 cm from each end of the pocket, make diagonal cuts (“dog’s ears”). Turn the off-set welt and large pocket bag to the wrong side through the opening. Secure the ends of the pocket from the wrong side with double backstitching. Sew and serge the edges of the pocket bags.

2. Sew the shoulder seams. Sew the side seams together with the sleeve seams. Press seams toward the back and serge.
3. Sew the cuff into a ring. Fold the cuff in half lengthwise, right side out, and press. Sew the cuff to the sleeve, easing the sleeve as needed.
4. Sew the hood pieces together and serge the seam allowances. Turn the outer edge twice to the inside by 1 cm and topstitch. Sew the hood to the neckline and serge the seam allowances.
5. Serge the front band edges. Serge one long edge of the placket. Sew the un-serged edge of the placket to the sweatshirt, slightly stretching the placket. Insert the zipper. Fold the zipper with the placket and topstitch into the zipper joining seam. Turn the placket inside and topstitch into the upper edge joining seam.

Congratulations – your jacket are finished! :)