

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

Important! Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

4941 Sweatshirt with hood

Recommendations on fabric:
natural/mixed knit fabric of small stretchiness.

You will also need: two grommets,
two cord ends, decorative cord.

CUTTING:

The word, "beam" used on some patterns means "straight of grain". Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Main fabric:

1. Back – cut 1 on fold
2. Center front – cut 1 on fold
3. Side front – cut 2
4. Yoke – cut 2
5. Hood – cut 4
6. Off-set welt – cut 2
7. Sleeve – cut 2
8. Cuff – cut 2
9. Placket – cut 1 on fold



INSTRUCTIONS:

1. Fold off-set welt in half lengthwise right sides together and sew ends. Turn the piece right side out, straighten, press. Pin off-set welt onto side front according to markings and topstitch ends.
2. Sew side fronts to front, press towards center and serge.
3. Sew yoke to sleeve, press seam allowances towards yoke and serge.
4. Sew sleeves to back, press seams towards back and serge. Sew sleeves to front, press towards front and serge.
5. Sew side seams processing the sleeve seam at the same time, serge, and press.
6. Sew together pieces of hood by two. Install grommets on outer hood according to the markings. Pin hoods together right sides together and sew outer edge. Clip into curves, turn the piece right side out, straighten, press. Sew a decorative stitch along edge according to markings, making a casing. Pin right hood onto left hood and baste together along lower edge.
7. Sew hood into neckline, serge, and press.
8. Sew cuff into a ring, press seam apart. Fold cuff in half lengthwise right side out and press. Sew cuff to lower edge of sleeve, stretching it to the required length. Press towards top and serge.
9. Sew lower placket into ring, press seam apart. Pin together lower placket in half lengthwise right side out and press. Sew lower placket to lower edge, stretching it to the required length. Press towards top and serge.
10. Thread cord into hood, attach cord ends. Tip: you may also see ready cuffs and knit bands for cuffs and placket.

Congratulations, your sweatshirt is ready! :)