

If the pattern has a double line around it, the seam allowances are included.

**Note:** By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

**Important!** Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

## 4948 Double layer dress

Recommendations on fabric:  
natural/mixed fabric suitable for  
dresses.

You will also need: 5 buttons

### CUTTING:

The word, "beam" used on some  
patterns means "straight of grain".  
Some pieces will  
be cut on the fold, this is noted on  
the pattern piece. Mark all notches  
and other  
design features such as darts, pleats etc. from the pattern onto your fabric.



### Main fabric:

1. Outer back - cut 1 on fold
2. Inner back – cut 1 on fold
3. Outer front - cut 1 on fold
4. Inner front – cut 1 on fold
5. Sleeve - cut 2
6. Placket - cut 1

## INSTRUCTIONS:

1. Press seam allowances along the longer and one shorter side of placket onto wrong side. Pin packet onto outer front and topstitch.
2. Sew shoulder and side edges of outer and inner parts, press seams towards back and serge.
3. Pin wrong side of inner dress to right side of outer dress and sew the neckline. Clip seam allowances, turn dress right side out, straighten, press, baste together along armholes.
4. Sew sleeve seam, serge, and press. Sew sleeves into armholes matching notches, press seam, serge.
5. Press seam allowances along hem of dress and hem of sleeve onto wrong side at 1 cm, then again at 1 cm and topstitch.
6. Sew on buttons at placket.

Congratulations, your dress is ready! :)