

If the pattern has a double line around it, the seam allowances are included.

**Note:** By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

**Important!** Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

## 5002 Short-Sleeved Blouse Jacket

Recommendations on fabric: light blouse fabric of natural or mixed fibers.

You will also need: 3-4 buttons.

### CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.



Seam allowances: 1 cm for all seams.

### Main fabric:

1. One-piece -belt – 2 pieces
2. Collar – 2 pieces
3. Center back part – 2 pieces
4. Side back part – 2 pieces
5. Side front part – 2 pieces
6. Back neckline facing – 1 folded piece
7. Center front part – 2 pieces
8. Front band – 2 pieces

## 9. Sleeve – 2 pieces

### Fusing:

1. back neckline facing – 1 folded detail
2. front band– 2 details

### INSTRUCTIONS:

1. Stitch the one-piece belt along the long edges, then turn it right side out and press. Topstitch at 0.5 cm from the edge.
2. Sew center back and princess seams. Insert the one-piece belt into the princess seams.
3. Sew front princess seams.
4. Sew shoulder and side seams.
5. Place the front bands and front pieces right sides together, then pin them to the edges of the front bands. Stitch the front edges. Sew shoulder seams of the front bands and the back neckline facing.
6. Trim the collar along the outer contour. Sew the inner collar to the neckline, and the outer collar to the neckline facing. Press seam allowances open. From the inside, sew together the seam allowances of the inner collar and the back neckline facing.
7. Trim the hem of the jacket. Sew the front bands to the hem allowance.
8. Topstitch the jacket along the edges and the collar at 0.5 cm from the edge.
9. Sew sleeve seams. Finish sleeve hems and set in the sleeves, easing along the sleeve cap.
10. Make buttonholes on the right front; sew buttons on the left front.
11. Sew in shoulder pads.

Congratulations, your blouse-jacket is ready! :)