

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

Important! Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

5008 Jacket with Notched Collar

Recommendations on fabric: costume fabric.

You will also need: Lining, fusible interfacing, shoulder pads, 3 buttons..

CUTTING:

The word, "beam" used on some patterns means "straight of grain". Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Seam allowances: all seams 1 cm.

Main fabric:

1. Off-set welt – 2 pieces
2. Center back part – 2 pieces
3. Side back part – 2 pieces
4. Side upper front part – 2 pieces
5. Side lower front part – 2 pieces
6. Back neckline facing – 1 folded piece
7. Center front part – 2 pieces
8. Front band one-piece with outer collar – 2 pieces
9. Upper sleeve – 2 pieces



10. Lower sleeve – 2 pieces

Fusing: Front bands, back neckline facing, off-set welt.

INSTRUCTIONS:

1. Stitch center and princess seams on the back.
2. Fold the welt along the center. Tack the lower edges of the welt to the upper edge of the side lower front part. Stitch the side lower front part to the side upper front part, catching the welt. Stitch front princess seams, securing the side edge of the welt.
3. Stitch side and shoulder seams.
4. Stitch the center seam of the outer collar together with the front bands. Stitch the front shoulder seams and the back neckline facings. Clip seam allowances. Stitch the inner collar into the garment neckline; stitch the outer collar into the facing neckline. Trim seam allowances close to the stitch and press them apart.
5. Place front bands onto front pieces right sides together and pin them to the edges; pin the edges of the outer and inner collars together. Stitch the front edges and collar neatly. Sew the jacket hem. Sew the front bands to the hem.
6. Stitch sleeve seams. Finish sleeve hems and set in the sleeves, easing along sleeve caps.
7. Make buttonholes on the right front, sew buttons onto the left front.
8. Sew in shoulder pads.

Congratulations – your jacket are finished! :)