

If the pattern has a double line around it, the seam allowances are included.

**Note:** By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

**Important!** Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

## 5009 Blazer with Shawl Collar and Contrast Trim

Recommendations on fabric: suiting fabric.

You will also need: 3 buttons for closure, 6 buttons for sleeves, shoulder pads, and interfacing.

### CUTTING:

The word, "beam" used on some patterns means "straight of grain". Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.



Seam allowances: 3 cm on hems, 1 cm on all other seams.

### Main fabric:

1. Center back – cut 2
2. Side back – cut 2
3. Upper front – cut 2
4. Side lower front – cut 2
5. Back neck facing – cut 1 on fold
6. Center front – cut 2
7. Front facing/ one-piece with the collar – cut 2
8. Upper sleeve – cut 2

## 9. Lower sleeve – cut 2

### Decorative fabric:

1. Collar trimming – cut 1 on fold
2. Off-set welt for faux pocket – cut 2

Fusible interfacing: front facing, back neck facings, off-set welts.

### INSTRUCTIONS:

1. Sew side backs to center backs, serge, and press seams toward center. Sew center back seam. Serge and press seam toward left.
2. Fold the welt along the center. Baste the welt lower edges to the upper edge of the side lower front. Sew side lower front to side upper front, catching the welt. Serge and press seam up. Sew side fronts to center fronts, catching the welt side edge. Serge and press seams toward center.
3. Sew side and shoulder seams. Serge and press toward back.
4. Sew front facings together with back neck facings at shoulder seams. Clip into curves. Stitch inner collar into garment neckline; stitch outer collar into facing neckline. Trim joining seam allowance close to stitch and press them apart.
5. Pin front facings on front, right sides together. Pin edges of outer and inner collars together. Sew and clip into curves. Understitch where possible. Turn right side out and press. Sew decorative trim to neckline. Serge, press, and sew jacket hem. Sew front facings to hem.
6. Sew sleeve seams. Serge lower edge of sleeve, turn onto wrong side, and topstitch. Make a gathering stitch along sleeve caps for ease. Sew sleeves into armholes, matching marks and easing along sleeve caps.
7. Make buttonholes on right front, sew buttons on left one. Sew three decorative buttons on each sleeve.
8. Sew in shoulder pads.

Congratulations – your blazer are finished! :)