

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

Important! Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

5010 Jacket with Shawl Collar and Contrast Details

Recommendations on fabric: suiting fabrics.

You will also need: lining, fusible interfacing, button, contrast fabric.

CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.



Seam allowances: all seams 1 cm.

Main fabric:

1. Center back part – 2 folded pieces
2. Side back part – 2 pieces
3. Side front part – 2 pieces
4. Back neckline facing – 1 folded piece
5. Center front part – 2 pieces
6. Front band – 2 pieces
7. Upper sleeve – 2 pieces
8. Lower sleeve – 2 pieces

Another fabric:

1. Off-set welt – 2 pieces
2. Outer collar – 1 folded piece

Fusing:

1. Off-set welt – 2 pieces

2. Back neckline facing – 1 folded piece
3. Front band – 2 pieces
4. Outer collar – 2 pieces

Lining:

1. Upper sleeve – 2 pieces
2. Lower sleeve – 2 pieces
3. Center front part – 2 pieces
4. Center back part – 2 pieces
5. Side back part – 2 pieces
6. Side front part – 2 pieces

INSTRUCTIONS:

1. Sew back center and princess seams, sew front princess seams.
2. Fold the welt along the fold line, finish neatly along short edges. Stitch the lower edges of the welt to the front along the markings. Fold the welt out, press, and topstitch onto the front.
3. Sew side and shoulder seams.
4. Sew center seam of outer collar together with front facings. Sew shoulder seams of front facings and back neckline facings. Clip seam allowances. Sew inner collar to garment neckline; sew outer collar to facing neckline. Trim seam allowances close to the stitch and press them open.
5. Place front facings on front pieces, right sides together, and pin to edges. Pin edges of outer and inner collars together. Sew edges and collar neatly. Sew jacket hem. Attach front facings to hem.
6. Sew sleeve seams. Finish sleeve hems and sew sleeves into armholes, easing along sleeve caps.
7. Sew in shoulder pads.
8. Sew lining pieces together. Attach lining to sleeve hems, inner edges of front facings, and back neckline facing. Sew lining to hem.
9. Make buttonholes on the right front, sew buttons on the left front.
Congratulations – your jacket are finished! :)