

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

Important! Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

5012 Fitted blazer with rounded lapels

Recommendations on fabric: wool/semi-wool with artificial yarns.

You will also need: fusing; 3 buttons; lining.

CUTTING:

The word, "beam" used on some patterns means "straight of grain". Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.



Seam allowances: all seams 1 cm.

Main fabric:

1. Outer collar – 1 piece
2. Inner collar – 1 piece
3. Back part – 1 piece
4. Side back part – 2 pieces
5. Front part – 2 pieces
6. Side front part – 2 pieces
7. Upper sleeve – 2 pieces
8. Lower sleeve – 2 pieces
9. Front band – 2 pieces

10. Neckline facing – 1 piece

Lining:

1. Center back part – 1 piece
2. Side back part – 2 pieces
3. Side front part – 2 pieces
4. Center front part – 2 pieces
5. Sacking – 4 pieces
6. Upper sleeve – 2 pieces
7. Lower sleeve – 2 pieces

Fusing:

1. Front band
2. Back neckline facing
3. Side front part
4. Center front part
5. Center back upper part with armhole segment
6. Center back lower part
7. Side back part's armhole
8. Side back lower part
9. Lower sleeve hem
10. Upper sleeve hem, collar

INSTRUCTIONS:

1. Apply fusible interfacing to the wrong side of the following pieces: front band, back neckline facing, side front piece, center front piece, upper center back piece (including the armhole section), lower center back piece, side back armhole area, lower side back piece, lower sleeve hem, upper sleeve hem, and collar.
2. Stitch the horizontal bust dart.
3. Stitch the pocket bag to the side and center front pieces, right sides together, matching notches. Press the seam toward the pocket bag and topstitch on the pocket bag.
4. Stitch the front princess seams, including the pocket bag. Clip the seam allowances and press them open, pressing the pocket into place.
5. Stitch the facings to the front bands, turning at both the top and bottom. Clip the corners and turn the upper and lower corners right side out.
6. Stitch the back neckline facing to the front bands. Press the shoulder seams of the facing and front bands open.
7. Stitch the center back seam and the back princess seams. Press the seams open.
8. Stitch the garment shoulder and side seams. Press the seams open.

9. Place the outer collar and inner collar right sides together and stitch along the outer edge. Trim the corners and turn the collar right side out.
10. Stitch the center back seam of the outer collar and attach it to the neckline. Press the seam open.
11. Stitch the vertical dart, continuing into the collar seam.
12. Attach the inner collar. Press the vertical darts and the collar joining seam open.
13. Secure the collar joining seams.
14. Stitch the sleeve elbow seam and press it open.
15. Stitch the sleeve front seam and press it open.
16. Set the sleeves into the armholes, matching notches.
17. Stitch the lining pieces, leaving an opening in the right sleeve seam. Press the lining.
18. Sew in the shoulder pads.
19. Attach the lining to the front bands and back neckline facing, to the garment hem, and to the sleeve hems, matching lining seams to garment seams. Make 7 securing stitches above the seams along the garment hem.
20. Turn the garment right side out through the sleeve opening. Stitch the sleeve opening closed.
21. Make buttonholes on the right front and sew the buttons onto the left front.

Congratulations – your blazer are finished! :)