

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

Important! Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

5162 Faux fur waistcoat with collar.

Recommendations on fabric: artificial/nature fur of 150 cm width.

You will also need: lining of 150 cm width, fusing, 3 buttons.

CUTTING:



The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Main fabric:

Fur:

1. Center back part – 1 folded piece
2. Side back part – 2 pieces
3. Side front part – 2 pieces
4. Center front part – 2 pieces
5. Back Basque – 1 folded piece
6. Front Basque – 2 pieces
7. Collar – 4 pieces
8. Back neckline facing – 1 folded piece

Lining:

1. Center back part – 1 folded piece
2. Side back part – 2 pieces

3. Side front part – 2 pieces
 4. Center front part – 2 pieces
 5. Back Basque – 1 folded piece
 6. Front Basque – 2 pieces
- Fusing: center front lining.

INSTRUCTIONS:

1. Apply the fusing to wrong side of center front lining.
2. Stitch relieves in front and back and press them apart.
3. Stitch the front and back of the Basque accordingly onto the front and back pieces right sides together and press seam apart.
4. Stitch side seams and press them apart.
5. Stitch collars middle seams together. Stitch inner collar into fabric neckline. Press the seam apart.
6. Stitch back neckline facing to back lining. Stitch lining seams excluding shoulder seams. Stitch outer collar into lining neckline. Lay the lining and fabric details right sides together, stitch them together along contour/armhole contours leaving shoulder seams open. Slash rounding's at seams. Turn the details right side out.
7. Stitch fabric shoulder seams. Sew lining shoulder seams with blind stitches.
8. Make buttonholes into right edging, sew buttons on the left one.

Congratulations, your waistcoat is ready! :)