

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

Important! Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

5283 Shirt with Short Sleeves

Recommendations on fabric: crinkle chiffon.

You will also need: clue interfacing; 5 buttons.

CUTTING:

The word, "beam" used on some patterns means "straight of grain". Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.



Seam allowances: 1 cm for all seams.

Main fabric:

1. Front part – 2 details
2. Back part – 1 detail
3. Sleeve – 2 details
4. Collar – 2 details
5. Stand-up collar – 2 details

Clue interfacing: placket, outer collar, stand-up collar.

INSTRUCTIONS:

Press each stitched seam, then serge and press again.

1. Strengthen the placket, outer collar, cuffs, and stand collar with fusible interfacing.
2. Sew bust darts on the front piece and topstitch them.
3. Sew shoulder seams and topstitch.
4. Sew sleeves into armholes and topstitch the seams.
5. Serge side edges separately from the hem up to 15 cm, then sew together down to the notch marks.
6. Fold sleeve hem allowance twice to the wrong side at 3 cm width and topstitch at foot width. Press again and topstitch the lower edge of the fold at foot width.
7. Finish the placket.
8. Sew the inner and outer collars together, turn the collar right side out, and topstitch.
9. Sew the collar between the stand collar pieces.
10. Sew the inner stand (with collar) to the neckline. Fold the open edge of the outer stand under and topstitch along the seam of the inner stand.
11. Press the hem allowance to the left and topstitch. Press and topstitch the slit allowances.
12. Make buttonholes on the right (overlap) side and sew buttons onto the left (underlap) side.

Congratulations, your shirt is ready! :)