

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

Important! Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

5307 Top with tie band and open back

Recommendations on fabric: knit fabric (cotton, viscose)

You will also need: 3 buttons

CUTTING:

The word, "beam" used on some patterns means "straight of grain". Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.



Seam allowances: 1 cm on all edges, 2 cm on central back seam for sewing in zipper, 2 cm on hem.

Main fabric:

1. top - cut 2
2. tie - cut 1

INSTRUCTIONS:

1. Fold and press 1 cm of the hem of bottom edge to wrong side, for both tops.
2. Fold the tie along the center, right sides together, then stitch, turn out and stitch ends.

3. Stitch the neckline, right sides together.
4. Stitch the armholes, leaving an opening at the neck for the tie.
5. Stitch center back edges.
6. Turn the top right side out and press.
7. Stitch a channel along the neckline for the tie.
8. Pull the tie through the channel.
9. Match the folded edges of the bottom and topstitch. Topstitch around the edges of the rest of the top.
10. Work three buttonholes on back left and sew three buttons on right.

Congratulations, your top is ready! :)