

If the pattern has a double line around it, the seam allowances are included.

**Note:** By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

**Important!** Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

## 5316 Coat with contrast inserts

Recommendations on fabric: artificial leather of two colors.

You will also need: fusing, separable zipper, lining.

### CUTTING:

The word, "beam" used on some patterns means "straight of grain". Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.



Seam allowance: 1 cm for all seams.

### Main fabric:

1. Back yoke – 2 details
2. Middle back part – 2 details
3. Lower back part – 2 details
4. Back contrast insert – 2 details
5. Side lower back part – 2 details
6. Side upper back part – 2 details
7. Front yoke – 2 details
8. Middle front part – 2 details
9. Upper front part – 2 details
10. Upper side front part – 2 details

11. Lower side front part – 2 details
12. Front contrast insert – 2 details
13. Stand-up collar – 2 details
14. Front band – 2 details
15. Sleeve – 2 details
16. Sleeve back insert – 2 details
17. Sleeve front insert – 2 details

OUR ADVICE: if wished, you can cut contrast back and front inserts into additional segments, depending on the material length.

Lining:

1. Front piece - 2 details
2. Back - 2 details
3. Sleeve - 2 details

NOTE: Join all the front pattern pieces into one piece and cut the lining. In the same way, join the back and sleeve pattern pieces and cut the lining. The front and back of the lining must be cut minus the width of the facings.

Fusing:

1. Stand-up collar – 1 detail
2. Front band – 2 details
3. Back yoke – 2 details
4. Front yoke – 2 details
5. Seam allowances: sleeve, front contrast inserts, back contrast insert.

INSTRUCTIONS:

1. Strengthen the front band, stand-up collar, front yoke, back yoke, sleeve hem, front contrast insert hem, back contrast insert hem.
2. Overstitch the inner collar with outer one (right sides together) on the collar fall side.
3. Sew front yoke to front contrast insert. Make decorative stitch on 0.2 cm from front yoke joining seam.
4. Sew the middle front part to front contrast insert. Make decorative stitch on 0.2 cm from middle front part joining seam.
5. Sew lower front part to front contrast insert. Make decorative stitch on 0.2 cm from lower front part joining seam.

6. Sew upper side front part to front contrast insert. Make decorative stitch on 0.2 cm from upper side front part joining seam.
7. Sew the lower side part to contrast the front insert. Make decorative stitch on 0.2 cm from lower side front part joining seam.
8. Sew back yoke to back contrast insert. Make decorative stitch on 0.2 cm from back yoke joining seam.
9. Sew upper side part to back contrast insert. Make decorative stitch on 0.2 cm from upper side back part joining seam.
10. Sew middle back part to back contrast insert. Make decorative stitch on 0.2 cm from back yoke joining seam.
11. Sew lower back part to back contrast insert. Make decorative stitch on 0.2 cm from lower side back part joining seam.
12. Sew lower side back part to back contrast insert. Make decorative stitch on 0.2 cm from lower side back part joining seam.
13. Sew shoulder and side seams.
14. Sew inner stand-up collar to the neckline.
15. Fold the front parts right sides together coinciding yokes, then measure front edge lengths. Sew the zipper to the edges. Fold edges at zipper area under and press through pressing cloth.
16. Sew outer stand-up collar to the front band.
17. Fold the front band and front part right sides together. Overstitch ends of stand-up and front band, from the front part side. Sew lower edges of front bands to front part strictly along the marked line of hem turning-under. Cut front edge upper and lower corners Turn edges into right side, trim seams. Make decorative stitch on 0.5 cm from the edge.
18. Sew sleeve back insert to the sleeve. Make decorative stitch on 0.2 cm from back sleeve insert joining seam.
19. Sew sleeve front insert to the sleeve. Make decorative stitch on 0.2 cm from sleeve front

insert joining seam.

20. Sew sleeve edges. Sew sleeves into armholes according to notches.

21. Sew shoulder pads and sleeve heads into.

22. Sew seams into lining, then sew sleeves into, with a hole in the sleeve front seam. Sew sleeves into and press the lining.

23. Sew lining to front bands and outer stand-up inner edges. Press joining seam allowances apart, then sew near seam. Sew lining sleeves and garment hems to fabric ones.

Congratulations, your coat is ready! :)