

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

Important! Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

5571 Slouch blouse with bow on sleeves

Recommendations on fabric: Silk/viscose.

You will also need: Fusible interfacing, piping.

CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.



Main fabric:

1. Right front part – 1 piece
2. Left front part – 1 piece
3. Back part – 2 pieces
4. Side back part – 2 pieces
5. Collar – 2 pieces
6. Waistband – 2 pieces
7. Back sleeve – 2 pieces
8. Front sleeve – 2 pieces

Fusible interfacing: outer collar.

INSTRUCTIONS:

1. Apply the fusible interfacing to wrong side of outer collar.
2. Stitch front darts. Slash darts' depths and neaten them.
3. Stitch back relieves. Neaten them and press toward the back center.
4. Neaten blouse's side edges. Stitch side seams and press them apart leaving a hole in left seam. Topstitch the hole in left seam. Stitch shoulder seams, neaten them and press backwards.
5. Lay collars together. Overstitch the inner collar with outer collar, cut corner allowances and turn the collar right side out. Press the collar.
6. Stitch the waistband to the right/left front part. Neaten the seam.
7. Press the piping along the center. Overstitch edges of front neckline, waistband, front/back parts' hems, back sleeves' hems, sleeve shaped tie, front sleeves' hems, and shaped tie with piping.
8. Stitch sleeve seams and neaten them. Press sleeve seams.
9. Stitch the outer collar into neckline, fold inner collar's open edge under and topstitch it along joining seam.
10. Stitch sleeves easing them along sleeve caps. Neaten joining seams.

Congratulations, your blouse is ready! :)