

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

Important! Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

5803 Wrap tunic with shoulder gathers

Recommendations on fabric: middle/high stretch-knit jersey (natural or mixed).

You will also need: Hot-fix rhinestones that come with heatsensitive glue on the back.

CUTTING:

The word, "beam" used on some patterns means "straight of grain". Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Seam allowances: all seams 1 cm.

Main fabric:

1. Back – cut 2
2. Front – cut 1
3. Left front – cut 1
4. Yoke – cut 2
5. Sleeve – cut 2

INSTRUCTIONS:



Advice: sew knit pieces with special elastic/zig-zag stitches. If you use an overlock, cut seam allowances to 0.6-0.8 cm width. Topstitch hem allowances with double needle to save elasticity.

1. Make and sew pleats at 3 cm, according to the marked lines on the front. The inner pleat fold faces downward. Sew the left front to the front. Serge and press the seam. Make and sew the pleat on the left side. The seam must be in the inner pleat fold and face downward.
2. Sew the center back seam. Serge and press the seam toward the left.
3. Sew a gathering stitch along the upper front edges and gather. Sew the yoke to the front. Serge and press the seam toward the yoke.
4. Sew the shoulder seams. Serge and press seam allowances toward the back.
5. Trim the seam allowance at the notch on the front neckline. Serge the neckline edge, starting from the left front and ending at the notch on the right front. Fold the serged neckline edge to the wrong side and topstitch.
6. Sew the left front to the right front along the wrap edge and then vertically down. Trim the seam allowance at the lower corner, serge the seam, and press toward the right side. Topstitch along the wrap seam, meeting up with the neckline topstitching. Make a counter pleat from the extra loose fabric of the lower wrap and sew it on the wrong side.
7. Sew the front and back side seams. Serge seam allowances and press toward the back.
8. Sew the sleeve seams. Serge and press seam allowances.
9. Sew a gathering stitch along the sleeve cap for ease. Sew the sleeves into the armholes, matching notches and adjusting ease. Serge and press seam allowances.
10. Serge the garment and sleeve bottom edges. Fold to the wrong side, press, and topstitch.
11. Attach rhinestones in a decorative circle, imitating a buckle where the wrap meets the side front.

Congratulations – your tunic are finished! :)