

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.


Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

Important! Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

7002 Hoodie with Decorative Waistband

Recommendations on fabric: cotton or fleece.

You will also need: white flannel for lining, zipper (length depends on the sweatshirt size), 2 buttons of 14 mm diameter.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Seam allowances: all seams 1 cm.

Main fabric:

1. Front / hood – cut 1 on fold
2. Back – cut 1
3. Waistband – cut 2 on fold
4. Sleeve – cut 2
5. Front zipper cover – cut 1
6. Cuff – cut 2

Lining:

1. Front / hood – cut 1 on fold
2. Back – cut 1

3. Sleeve – cut 2

Note: Use main pattern pieces without changes to cut lining details for front/hood, back and sleeves.

INSTRUCTIONS:

1. Sew the center hood seam. Press the seam toward the left side and topstitch 0.5 cm from the seam.
2. Sew the shoulder seams. Press the seams toward the back and topstitch 0.5 cm from the seam.
3. Sew the hood dart. Sew the lower edge of the hood to the neckline, matching the center markings.
4. Sew the sleeves into the armholes, matching the notches. Press the seams toward the armholes and topstitch 0.5 cm from the seam.
5. Sew the side seams and sleeve seams.
6. Cut the slit for the zipper on the front.
7. Open the zipper. Pin the zipper halves to the slit from the right side according to the markings.
8. Sew the lining pieces following the same steps as for the main fabric.
9. Place the lining and sweatshirt right sides together and sew along the zipper edges (attaching the zipper), hood edges, hem, and side slit edges. Turn right side out, straighten, press, and sew a double decorative stitch.
10. Sew a securing stitch along the neckline, joining the main garment and the lining.
11. Baste the sleeve hem together with the lining.
12. Sew the cuff into a ring and press the seam open.
13. Sew one edge of the cuff to the sleeve hem, right sides together, matching the edges. Fold the cuff in half lengthwise with the wrong side inward, turn the open edge under, and sew it to the sleeve hem. Topstitch decoratively 0.5 cm from the edge.
14. Turn the edges of the zipper cover under and sew it to the front according to the markings.
15. Place the waistband pieces right sides together and sew around all edges, leaving a small opening. Turn right side out, press, and topstitch 0.5 cm from the edge.
16. Place the waistband on the front from the right side according to the markings, matching the notches, and sew it to the edges of the front side slits. The waistband overlaps the side slits and extends around to the back.
17. Make buttonholes at the ends of the waistband according to the markings.
18. Sew the buttons to the back.

Congratulations – your hoodie are finished! :)